| Setup Shee   | t   | Driver_  | Paul Upton  |  |
|--|---|--|---|--|
|  |   | ble at   | City General Astrot Date                                    |  |
| Conditions  ☑ High traction ☐ Clay                 | □ Smooth □ Sandy □ Wet                      | ☑ Bumpy<br>□ Soft dirt<br>☑ Dry                                    | ☐ Low traction☐ Grass☐ Dusty                                | ☐ Med traction☐ Hard soil☐ Other   |
| Front Suspension  Ride height                      | # Washersmm                                 | Camber 1.0°  1 2  # Was  | Out (-) 0.0° ep Spacer 2.0 Caster 25° 230°  E               | Spring(color)  Black  Oil 500 wt  Piston #1.4  Kit pistons  drilled to  1.4mm  holes             |
| Rear Suspension                                    | Shock Mounting  Wheelbase Long Medium Short |  | Aluminum(Opt)  # Washers                                    | Spring(color)  Spring(color)  Black  Oil 400 wt  Piston #  Kit pistons  drilled to  1.4mm  holes |
| Front Tires&Wheels Front Tires Schumac Inserts n/a | L   | <i>bs</i> Rear Til   | ires&Wheels<br>res <u>Schumacher Yell</u><br>Schumacher Med |  |
| Servo_ Esc_ Batteries_                             |   | Motor  Motor/_  Pinion/Spur/_                                      | _   | Other  Angle   4° □ 10°  |
| Thresher AKX2 con                                  | version fitted.                             | xles to narrow front<br>Long wheelbase, 3.0<br>side configuration. | mm side plates fitt   |  |