TCDZ				
SETUP SHEET for th	e TeamC TC02C EVO		Date//	
Conditions ☐ High traction ☑ Clay	□ Smooth □ Bu □ Sandy □ So □ Wet □ Dry	ft dirt	ction	
Front Suspension Shock Mounting & Camber link Front Shocks				
Ride height Arm leve	Washers Camber <u>1mm</u> mm <u>1</u>	Toe-in (+)/Out (-)° Bump Steep Spacer Caster ✓ 25° □ 30° # Washers ↓ ↓ ↓ ↓ ↓ ↓ ↓	Spring(color) Black Solution Solution Spring(color) Black Solution So	
Rear Suspension	Shock Mounting & Camber line Anti-roll bar: mm Camber1.5° Anti-Squat°	k Aluminum(Opt)	Rear Shocks Spring(color) Black Soft 3 dot OilOut Limiters InOut2 holes drilled To 1.4 mm	
Diff Teamc	Tires&Wheels	Deer Ic di	irtweb gold	
Brand Oil wt ^{Half full 1000 wt}	Front <u>Jc dirtweb gold</u> Stock Notes <u>Inserts</u> Wheel	Notes		
Electronics	Motor ^{Absi}	ma 8,5 turns	Body & Wing	
Servo Combat series ESC Absima Setting	Pinion/Spur_2	deg 6 / Std bsima shorty	Body <u>TeamC</u> Wing <u>^{TeamC}</u> Wing Angle □ 4° ⊈ 10°	
CommentsWorked on diff to made it smooth Shorty to the rear. No extra weight 4deg rear aloy blockArn0				