

# Setup Sheet



Driver Robert Jaques  
 Track / City A1-Racing - Arena X  
 Event Rd3 Date 16 / 01 / 12

Editable by Robert Jaques & Am0 at Petitr.com

Conditions			
<input type="checkbox"/> High traction	<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Bumpy	<input type="checkbox"/> Low traction
<input type="checkbox"/> Clay	<input type="checkbox"/> Sandy	<input type="checkbox"/> Soft dirt	<input type="checkbox"/> Grass
	<input type="checkbox"/> Wet	<input type="checkbox"/> Dry	<input type="checkbox"/> Dusty
			<input checked="" type="checkbox"/> Med traction
			<input type="checkbox"/> Hard soil
			<input checked="" type="checkbox"/> Other <u>Carpet</u>

### Front Suspension Shock Mounting & Camber link

Toe-in (+)/Out (-) 0°  
 Bump Steep Spacer 0  
 Camber -2°  
 Caster  25°  30°  
 # Washers 2 mm  
 # Washers 1 mm

Ride height Wishbones Level

### Front Shocks

Spring(color)  Black  Ans Blue  
 Oil Sch 40 wt  
 Piston # white

### Rear Suspension Shock Mounting & Camber link

Wheelbase  Long  Medium  Short  
 Camber -2°  
 Aluminum(Opt)    
 # Washers 1 mm  
 Normal   
 # Washers 1 mm

Ride height Drive shafts level

### Rear Shocks

Spring(color)  Black        
 Oil los 27.5 wt  
 Piston # drilled white  
 (pistons drilled to 1.4MM)

### Front Tires & Wheels

Front Tires Schumacher Blue Mini Pins  
 Inserts -      Wheels HPI

### Rear Tires & Wheels

Rear Tires Schumacher Blue Mini Pins  
 Inserts -      Wheels HPI

### Radio/Batteries

Servo Savox  
 Esc LRP  
 Batteries Orion

### Motor

Motor Novak SS 10.5  
 Pinion/Spur 21 / 80

**Comments** Notes Ansmann under lipo weight fitted . Rudebits under servo weight fitted 70gr. Shocks buggy Bodies / Truck shafts. Track Multi surface, 100% carpet. 2mm spacer fitted under RF wishbone hanger to give more anti-squat.