



	Setup Sheet					
Name:	Date:		Eve	nt		
Track Indoor ☐ Outdoor ☐ Size: Sm	all□ Medium	□ Large	Trac	tion: Low	/ □ Med □] High 🗌
Surface: Smooth□ Bumpy□ Rutted□	Type: Loose	/Loamy	☐ Hard F	Pack 🗌 Blu	ie Groove [□ Clay □
Bumpsteer//Adkerman/Servo Saver:	Co	ndition:	Dusty□] Dry□ W	⁄et □ Mudo	dy□
# washers over	front		Turns		Shocks	
over under under	middle		from fully	- au	FRONT	REAR
under # washers	rear		tight	OIL		
Front End:		ension:	REAR	BRAND		
8^{1}_{2}	RIDE HEIGHT	ONT	NEAN	PISTON		
8 ³ ₄	CAMBER			SPRING		
	SWEEP			REBOUND	%	%
45	KICK UP	-		STD/EMUL/VENT		
06				NOTES:		
	ANTI-SQUAT			M	res/Whee	
	TOE (in/out)			DDAND/TDFAD	FRONT	REAR
"A" Block	SWAY BAR SHOCK LENGTH			BRAND/TREAD		
(0° WITH CENTER DOT INSERT)	(DROOP)	 Mounts	o	COMPOUND		
Composite Aluminum	BODY MAKE		5	INSERT		
"B" Block	DOD'I MAKE		-	WHEEL		
(10° WITH CENTER DOT INSERT)				Differential Oil:		
Composite Aluminum				FRONT	CENTER	REAR
Rear End:						
			Ħ	[Electronics	<u> </u>
A B C	Fron	it 🗀	(Height)	ESC:		
	A	8		Battery:		
8 ² ₃	-			Motor:		
\$\frac{4}{5}\$				Radio:		
6 6 6 6 6 6 6 6 6 6			H	Servo:		
			H		Drivetrain:	•
	Rear	ō	(Height)	PINION SIZE		(teeth)
"C" Block	Whe	elbase:		<u> </u>	i nassis Brac	
(3° WITH CENTER DOT INSERT)				Front	Middle 🔲	Rear
Composite Aluminum (-1°)			mm /FRONT	(front bra	ce is always recon	nmended)
"D" Block					Notes:	
(3° WITH CENTER DOT INSERT) Composite		_	mm /REAR			
(Rear Toe) Aluminum		large 2	<u>!mm</u>			
0° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 5° 1° 1° 1° 5° 1° 1° 1° 5° 1° 1° 1° 5° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1°		small 1	_ mm			