X – 5 Set-Up Sheet			
Driver:			Date:
Track:			
Tight/Open 1=very tight 5=very open	Wet/Dry 1=very wet 5=very dry	Smooth/Rough 1=very smooth 5=very rough	Slippery/High-Bite 1=very slick 5=very high bite
Front			
Suspension			Shocks
Ride Height:			Losi
Camber: ° Toe: In ° Out °			
Camber Link: Inside:			Mounting (Top/Bottom)://
Castor Block Height: Std/Cut: Washers:			Spring:
Roll Bar: Size:			Piston: Std /Drilled
Diff/One Way/Spool: Driveshafts:			Oil:
Outdrives Plastic/Metal:			Limiting (In/Out):/
CVD's/LCD's:			Internal Spring:
Washers Under Bellcranks: Under Knuckle Arms:			
Steering Ackerman In/Out :			
Rear			
Suspension			Shocks
Rear Hanger flipped: Antisquat:°			Losi
Ride Height: <u>Drivshafts just below level</u>			Oil Make:
Camber:° Toe In:°			Mounting (Top/Bottom):/
Camber Link: Inside: Outside: Hinside/8=outside Bottom Outside: A=inside Hub Spacing (Long/Medium/Short):			Spring:
			Piston: Std/Drilled
Diff (Plastic/Metal): Roll Bar: Size:			Oil: <u>30wt</u>
Driveshafts (Dogbone/CVD's Ally/Steel):			Limiting (In/Out):/
Other			
Notes:			
Front Tire:			
Rear Tire: Dinion/Spure /			
Motor: Pinion/Spur:/			