




Ride Height: _____ Axles: ☐ Trailing ☐ Inline
 Camber: _____ ° Toe: _____ ° Caster Block:
 Ackermann: ☐ Fwd ☐ Back ☐ 20° ☐ 25° ☐ 30°



Washers



Bumpsteer Washers:

Caster Block Position:
☐ Fwd ☐ Back
 Maneuvered Fwd:

Ride Height: _____

Trans Height: _____ Trans Brace: ☐

Camber: _____° Sway Bar: _____




Hinge Pin Brace Spacer: ☐ 0 ☐ 1mm ☐ 2mm ☐ 3mm

Rear Hub Carrier:
☐ 0° ☐ 0.5° ☐ 1.0° ☐ 1.5°


Arm Position:
☐ Back ☐ Mid ☐ Fwd



Washers



Anti-Squat:



Hub Position:

☐ Back ☐ Mid ☐ Fwd

A diagram of a vehicle chassis with several callout boxes for identification. A blue circle in the top left contains the word "Weight". Callout boxes are located at the front, rear, and along the sides of the chassis, pointing to various structural components.

Total Weight:

Rear Weight Bias: %

Gearing: /

Motor:

Slipper: ☐ 2 pads ☐ 3 pads

Diff Setting:

Battery:

Battery Placement:
