$X - 6^2$ Set-Up Sheet	
Driver: Ellis Stafford	Date: 28/29-3-09
Track: Worksop Indoors	
Tight/Open Wet/Dry Smooth/F	every rough 1=very slick 5=very high bite
Front	
Suspension	Shocks
Ride Height: <u>Arms just above level 26mm</u>	Losi ⊠/Associated □ Oil Make: Losi
Camber: $\underline{-1}^{\circ}$ Toe In/Out: \underline{Out} $\underline{1}^{\circ}$	on Make. <u>2001</u>
Camber Link: Inside: $\frac{1}{1=\text{inside}}$ Washers: $\frac{4}{4}$ Outside: $\frac{A}{A=\text{inside}}$	Mounting (Top/Bottom): <u>2/2</u> _{1=inside}
Caster Block (20°/25°/30°): <u>30</u> °	Spring: <u>Green</u>
Castor Block Position (Forward/Back): Forward	Piston: Red Std/Drilled Standard
Bump Steer Spacers 0.05" (Stock 2)/Other: 2	Oil: <u>35wt</u>
Spacers under inner Tie-Rod Ballstud: <u>0</u>	Limiting (In/Out): <u>0mm/</u>
Axle Trailing (Trailing/Inline) : <u>Trailing (stock)</u>	
Axle Height Top/Middle/Bottom: <u>Bottom</u>	
Steering Ackerman Forward (stock)/Back: Forward (stoc	<u>k)</u>
Servo Position: <u>Forward</u>	
Rear	
Suspension	Shocks
Transmission Height (Multiples of 0.3"): <u>0 Lowest</u>	Losi ⊠/Associated □
Ride Height: <u>Arms level 26mm</u>	Oil Make: Losi
Ride Height. Aims level 20min	
Camber: $\underline{-1}^{\circ}$ Toe Bar $3^{\circ}/4^{\circ}$: $\underline{4^{\circ}}$ Antisquat: $\underline{4^{\circ}}$	Mounting (Top/Bottom): 3/1
	Mounting (Top/Bottom): 3/1
Camber: $\underline{-1}^{\circ}$ Toe Bar $3^{\circ}/4^{\circ}$: $\underline{4^{\circ}}$ Antisquat: $\underline{4^{\circ}}$	Mounting (Top/Bottom): 3/1 Spring: Pink
Camber: <u>-1</u> ° Toe Bar 3°/4°: <u>4°</u> Antisquat: <u>4°</u> Extra Hub Toe In/Out: <u>No/</u> Rear Roll Bar: <u>Yes</u> Size: <u>0.9mm</u>	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard
Camber: <u>-1</u> ° Toe Bar 3°/4°: <u>4°</u> Antisquat: <u>4°</u> Extra Hub Toe In/Out: <u>No/</u>	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard Oil: 30wt
Camber: -1° Toe Bar 3°/4°: 4° Antisquat:4° Extra Hub Toe In/Out: No/ Rear Roll Bar: Yes Size: 0.9mm Camber Link: Inside: E Speed High Outside: B Washers Under Inner Ballstud: 0	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard
Camber: -1° Toe Bar 3°/4°: 4° Antisquat:4° Extra Hub Toe In/Out: No/ Rear Roll Bar: Yes Size: 0.9mm Camber Link: Inside: E Speed High Outside: B Washers Under Inner Ballstud: 0 Hub Spacing Forward/Middle/Back: Back	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard Oil: 30wt
Camber: -1° Toe Bar 3°/4°: 4° Antisquat: 4° Extra Hub Toe In/Out: No/ Rear Roll Bar: Yes Size: 0.9mm Camber Link: Inside: E Speed High Outside: B Washers Under Inner Ballstud: 0 Hub Spacing Forward/Middle/Back: Back Arm Spacing Forward/Middle/Back: Forward	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard Oil: 30wt
Camber: -1° Toe Bar 3°/4°: 4° Antisquat:4° Extra Hub Toe In/Out: No/ Rear Roll Bar: Yes Size: 0.9mm Camber Link: Inside: E Speed High Outside: B Washers Under Inner Ballstud: 0 Hub Spacing Forward/Middle/Back: Back Arm Spacing Forward/Middle/Back: Forward Other	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard Oil: 30wt Limiting (In/Out): 0mm/
Camber: -1° Toe Bar 3°/4°: 4° Antisquat: 4° Extra Hub Toe In/Out: No/ Rear Roll Bar: Yes Size: 0.9mm Camber Link: Inside: E Speed High Outside: B Washers Under Inner Ballstud: 0 Hub Spacing Forward/Middle/Back: Back Arm Spacing Forward/Middle/Back: Forward Other Notes: Long axles fitted. Lipo fitted. 106g in front servo	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard Oil: 30wt Limiting (In/Out): 0mm/
Camber: -1° Toe Bar 3°/4°: 4° Antisquat: 4° Extra Hub Toe In/Out: No/ Rear Roll Bar: Yes Size: 0.9mm Camber Link: Inside: E Speed High Outside: B Washers Under Inner Ballstud: 0 Hub Spacing Forward/Middle/Back: Back Arm Spacing Forward/Middle/Back: Forward Other Notes: Long axles fitted. Lipo fitted. 106g in front servo Front Tire: Schumacer Yellow minipins 1 inner and oute	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard Oil: 30wt Limiting (In/Out): 0mm/
Camber: -1° Toe Bar 3°/4°: 4° Antisquat: 4° Extra Hub Toe In/Out: No/ Rear Roll Bar: Yes Size: 0.9mm Camber Link: Inside: E Speed High Outside: B Washers Under Inner Ballstud: 0 Hub Spacing Forward/Middle/Back: Back Arm Spacing Forward/Middle/Back: Forward Other Notes: Long axles fitted. Lipo fitted. 106g in front servo Front Tire: Schumacer Yellow minipins 1 inner and oute Rear Tire: Schumacer Yellow minipins	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard Oil: 30wt Limiting (In/Out): 0mm/ area and 60g under speedo.
Camber: -1° Toe Bar 3°/4°: 4° Antisquat: 4° Extra Hub Toe In/Out: No/ Rear Roll Bar: Yes Size: 0.9mm Camber Link: Inside: E Speed High Outside: B Washers Under Inner Ballstud: 0 Hub Spacing Forward/Middle/Back: Back Arm Spacing Forward/Middle/Back: Forward Other Notes: Long axles fitted. Lipo fitted. 106g in front servo Front Tire: Schumacer Yellow minipins 1 inner and oute Rear Tire: Schumacer Yellow minipins Motor: X12 6.5 Rear Wing: X6 no gurney but moved forward and low	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard Oil: 30wt Limiting (In/Out): 0mm/
Camber: -1° Toe Bar 3°/4°: 4° Antisquat: 4° Extra Hub Toe In/Out: No/	Mounting (Top/Bottom): 3/1 Spring: Pink Piston: Red Std/Drilled Standard Oil: 30wt Limiting (In/Out): 0mm/ area and 60g under speedo. r removed