

| | | | | | |
|-----------------|------|------|-----|----------|-----------|
| Driver: | | | | Date: | |
| Track/Location: | | | | Event: | |
| Tight/ | Open | Wet/ | Dry | Smooth/ | Rough |
| | | | | Slippery | High-Bite |

FRONT

| SUSPENSION | SHOCKS |
|--|--|
| RIDE HEIGHT: _____ | ASSOCIATED/ LOSI |
| CAMBER: _____ ° TOE: _____ ° IN/ OUT | MOUTING(T/B): _____ / _____ <small>1=inside</small> |
| CAMBER LINK: INSIDE _____ WASHERS _____ OUTSIDE _____ <small>1=inside A=inside</small> | SPRING: _____ |
| CASTER BLOCK: 20° 25°(stock) 30° | PISTON: _____ |
| BACK FORWARD (stock) | STANDARD/ DRILLED |
| BUMP STEER SPACERS: .050" (stock)/ OTHER: _____ <small>(spacers under outer tie-rod ballstud)</small> | OIL: _____ |
| AXLE: TRAILING(stock)/ INLINE | LIMITING(T/B): _____ / _____ |
| AXLE HEIGHT: TOP MIDDLE BOTTOM | |
| STEERING ACKERMAN: FORWARD(stock) BACK | |

REAR

| SUSPENSION | SHOCKS |
|--|--|
| TRANSMISSION: 4 Gear(Stock)/ 3 Gear | ASSOCIATED/ LOSI |
| TRANSMISSION HEIGHT: .060(stock)/ OTHER: _____ | MOUTING(T/B): _____ / _____ <small>1=inside</small> |
| RIDE HEIGHT: _____ | SPRING: _____ |
| CAMBER: _____ ° TOE BAR: 3° 4° ANTISQUAT: _____ | PISTON: _____ |
| CAMBER LINK: INSIDE: _____ WASHERS: _____ OUTSIDE: _____ <small>1=inside A=inside</small> | STANDARD/ DRILLED |
| HUB SPACING: FORWARD MIDDLE BACK | OIL: _____ |
| ARM SPACING: FORWARD MIDDLE BACK | LIMITING(T/B): _____ / _____ |

OTHER

| | |
|--------------|----------------------------|
| FRONT TIRES: | FRONT INSERTS: |
| REAR TIRES: | REAR INSERTS: |
| ESC: | MOTOR: |
| BATTERY: | PINION/SPUR: _____ / _____ |
| WING: | |

