X – 6 Set-Up Sheet			
Driver: Arjan van de Graaf (aka Janus)			Date:
Track: Charlerdinges			
Tight/Open 1=very tight 5=very open 4	Wet/Dry 1=very wet 5=very dry 3	Smooth/Rough 1=very smooth 5=very rough 2	Slippery/High-Bite 1=very slick 5=very high bite 2 / 4
Front			
Suspension			Shocks
Ride Height: 14,4 mm from top			Losi X/Associated
Camber: 1° Toe In/Out: Out 1,5°			Oil Make: AE
Camber Link: Inside: $\underline{2}$ Washers: $\underline{3}$ (thin) Outside: \underline{C} (GT-2) \underline{A} = inside			Mounting (Top/Bottom): $\underline{2} / \underline{O}$
Caster Block (20°/25°/30°): 25°			Spring: Bleu
Castor Block Position (Forward/Back): <u>FWD</u>			Piston: Red Std/Drilled Std
Bump Steer Spacers 0.05" (Stock 2)/Other: 1			Oil: <u>30</u>
Spacers under inner Tie-Rod Ballstud: <u>0</u>			Limiting (In/Out): $\underline{2} / \underline{0}$
Axle Trailing (Trailing/Inline): Inline, mounted to front			
Axle Height Top/Middle/Bottom: MID			
Steering Ackerman Forward (stock)/Back: <u>Back</u>			
Rear			
Suspension			Shocks
Transmission Height (Multiples of 0.3"): <u>0.090</u>			Losi X/Associated
Ride Height: 20,8 mm from top			Oil Make: AE
Camber: $\underline{1,5}^{\circ}$ Toe Bar $3^{\circ}/4^{\circ}$: $\underline{4}$ Antisquat: 2 thin, 1 thick			Mounting (Top/Bottom): $\underline{2}$ / \underline{M}
Extra Hub Toe In/Out: - 0,5 Reversed RE			Spring: Red
Camber Link: Inside: $\underline{\underline{2}}$ Outside: $\underline{\underline{B}}$ A=inside			Piston: Red Std/Drilled Std
			Oil: <u>35</u>
Washers Ballstud: Inside: 1 (thin) Outside: 3 Hub Spacing Forward/Middle/Back: FWD			Limiting (In/Out): $\underline{3} / \underline{0}$
Arm Spacing Forward/Middle/Back: <u>FWD</u>			
Anti-Roll Bar: Nope			
Other			
Notes/rants/excuses: Outdoor Carpet track, pretty large, good grip except for "black spots"			
Front Tire: Stagger Yellow (dremel); no insert; Narrow, WZ mount			
Rear Tire: MiniPin Yellow; Losi Red insert; wide wheel			
Weights: 15 Grams near motor, Alu front bulkhead			
Motor: 4.5 Pinion/Spur: <u>18 / 81</u>			
Wing: mounted to front ½ gurney			