2WDRC.com X-6 SET	UP SHE	X-FACTOR XFactoryR	
Driver:		Date:	0.00111
Track/Location:		Event:	
Tight/ Open Wet/ Dry Smoo	th/ Rough	Slippery High	n-Bite
FR	ONT		
SUSPENSION		SHOCKS	
RIDE HEIGHT:		_ ASSOCIATED/ LOS	SI
CAMBER:° TOE:° IN/ OUT		MOUTING(T/B):/_	
CAMBER LINK: INSIDE WASHERS	OUTSIDE	- SPRING:	
CASTER BLOCK: 20° 25° (stock) 30°		PISTON:	
BACK FORWARD (stock)		STANDARD/ DF	
BUMP STEER SPACERS: .050" (stock)/ OTHER: (spacers under outer tie-rod ballstud)		OIL:	
AXLE: TRAILING(stock)/ INLINE		LIMITING(T/B):/_	
AXLE HEIGHT: TOP MIDDLE BOTTOM		1 oz of weight on and around the b	oulkhead
STEERING ACKERMAN: FORWARD(stock) B			
SUSPENSION	EAR	SHOCKS	
303F EN310N		SHOCKS	
TRANSMISSION: 4 Gear(Stock)/ 3 Gear		ASSOCIATED/ LOS	SI
TRANSMISSION HEIGHT: .060(stock)/ OTHER:		MOUTING(T/B):/_	
RIDE HEIGHT:		_ SPRING:	
CAMBER: ° TOE BAR: 3° 4° A	NTISQUAT:	· · · · · · · · · · · · · · · · · · ·	
CAMBER LINK: INSIDE: WASHERS:	OUTSIDE: A=inside	-	RILLED
HUB SPACING: FORWARD MIDDLE B	ACK	OIL:	
	ACK	LIMITING(T/B):/_	
01	HER		
FRONT TIRES:	FRONT INSE	RTS:	
REAR TIRES:	REAR INSER		
ESC:	MOTOR:		E //
BATTERY:	·	PINION/SPUR:/	11)
WING:			