

RACE	5. Alpencuplauf		
TRACK	RC Club Wyland Andelfingen		
NAME	Patrick Vogt	DATE	14.08.2016

LAPS		BEST LAP TIME	19.066 sec
QUALIFYING POSITION	1.	FINAL POSITION	1.

TRACK SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> TIGHT
TRACK TRACTION	<input checked="" type="checkbox"/> HIGH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> LOW
TRACK SURFACE	<input checked="" type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TRACK TYPE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY
	<input type="checkbox"/> CARPET	<input type="checkbox"/> BLUE GROOVE	<input checked="" type="checkbox"/> ASTRO TURF
			<input type="checkbox"/> GRASS
TRACK CONDITION	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> WET
			<input type="checkbox"/> MUD

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input checked="" type="checkbox"/>	BALL DIFF <input type="checkbox"/>
OIL 10k cst	OIL cst	OIL 7k cst
SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
CROWN GEAR	SLIPPER	CROWN GEAR
COMPOSITE <input type="checkbox"/>	1 mm	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	SLIPPER ADJUSTMENT	STEEL <input checked="" type="checkbox"/>
ALU <input type="checkbox"/>		ALU <input type="checkbox"/>

COMPOSITE <input type="checkbox"/>	<input type="checkbox"/> PINION	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	STEEL <input checked="" type="checkbox"/>

GEARING		
PINION	19 T	SPUR GEAR
		81 T

FRONT	SHOCKS	REAR
3dot	SPRINGS	2dot
cst 600 Hudy	OIL	450 Hudy cst
% 5	REBOUND	5 %
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.0mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.2mm	<input type="checkbox"/> 6 HOLES
	<input type="checkbox"/> ø1.3mm	
	<input type="checkbox"/> ø1.4mm	
	CUSTOM PISTONS	
	ø 1.6 mm	ø 1.7 mm

FRONT	ANTI ROLL BAR	REAR
1.6 mm	THICKNESS	1.6 mm

FRONT	TIRES	REAR
Wide Stagger	TYPE	Minipin
medium	INSERTS	medium
12mm	WHEELS	12mm

ELECTRONICS		
MOTOR	6.5T	R10 Pro
TIMING	80%	Shorty 4500
		SPEEDO BATTERIES

ELECTRONICS LAYOUT		
SERVO POSITION	LEFT <input type="checkbox"/>	RIGHT <input checked="" type="checkbox"/>
MOTOR POSITION	FRONT <input checked="" type="checkbox"/>	REAR <input type="checkbox"/>
SPEEDO POSITION	LEFT <input checked="" type="checkbox"/>	RIGHT <input type="checkbox"/>
RECEIVER POSITION	LEFT <input type="checkbox"/>	RIGHT <input checked="" type="checkbox"/>
BATTERY POSITION	FRONT <input checked="" type="checkbox"/>	REAR <input type="checkbox"/>

COMMENTS

rear:1 row
inside/outside cutted

