

YZ4-F2 DTM2 CAL2

SETTING SHEET Ver.01

CIRCUIT

- INDOOR OUTDOOR
DIRT ASTROTURF CARPET GLASS WOOD
WET DRY DUSTY SMOOTH BUMPY
HARD PACKED CLAY BIUE GROOVE _____
LOW TRACTION MED TRACTION HIGH TRACTION

DRIVER

DATE

FRONT

Flat
 Gull
 Z2-017D(Plastic)

Aluminum ODTM2
 OCAL2

CAMBER \leftrightarrow _____ °
 TOE IN OUT _____ °
 RIDE HEIGHT _____ mm

Wide Narrow
 Aluminum
 Plastic

Z2-008GF2
 Flat Graphite

S (Plastic)
 B2-300FLS(Steel)
 Z2-300FLO(Aluminum)
 Z2-300FL5

Graphite Z2-415AO
 Graphite Hard
 4.30
 5.00

0°
 2.5°
 5°

Aluminum
SPRING
 GREEN (YS-A775)

OIL
 # _____
 ϕ 1.6x2 (BM-S162)

mm x _____
 mm x _____

REAR

CAMBER \leftrightarrow _____ °
 RIDE HEIGHT _____ mm

Z2-300RUM (Aluminum)

Z2-008RS3
 S4-008RS4

Z2-415R0

STD
 -2

Z2-302S2
 Z2-302S1

0.5
 1
 1.5

FF 05 FR 05 1

Aluminum
SPRING
 GREEN (YS-A1200)

OIL
 # _____
 ϕ 1.7x2 (BM-S172)

mm x _____
 mm x _____

DRIVE

3 gear 4 gear

Standard Graphite
 Z2-018BMA (Aluminum)

5mm x _____
 10mm x _____
 20mm x _____

5mm x _____
 10mm x _____
 20mm x _____

MOTOR \rightarrow _____ Rotor _____ mm
 GEAR \rightarrow Spur T / Pinion T : 2.6
 BATTERY \rightarrow _____
 ESC \rightarrow _____
 SETTING \rightarrow _____

YT-RW25
 Z2-BWR30

TIRE

FRONT
 TIRE \rightarrow _____
 INSERTS \rightarrow _____
 WHEELS \rightarrow _____

REAR

TIRE \rightarrow _____
 INSERTS \rightarrow _____
 WHEELS \rightarrow _____

OTHER

COMMENT