YZ-2 DT SETTING SHEET Ver.01

DRIVER	Team setup	DATE	2016/03/30

CIRCUIT TRS Circuit

○ INDOOR ● OUTDOOR
○ WET ● DRY ● DUSTY ○ OTHER
● LOW TRACTION ○ MED TRACTION ○ HIGH TRACTION
○ SMOOTH ● BUMPY ○ BIUE GROOVE ○ ASTROTURF
○ CARPET ○ WOOD

FRONT

○ Flat
○ Gull
● Z2-017D(Plastic)

2 mm

○ Z2-300FU
○ S (Plastic)
● N (Plastic)

● Flat ○ Gull
● Graphite

○ Graphite
○ Z2-415A

○ Graphite
○ 4.3
● 5.0
mm

1 mm
2 mm

g ○ Z2-300FL0
○ Z2-300FL5
○ B2-300FL(Steel)
● S (Plastic)

◆CAMBER ●←→○ 1 °
◆TOE ○IN ●OUT 0.5 °
◆RIDE HEIGHT 23 mm

2 mm
○ 0°
○ 2.5°
● 5°

○ ____ mm

mm
22 mm

SPRING
○ YELLOW (YS-A875)
● RED (YS-A850)

OIL
AE #30
○ #1 ○ #2 ○ #3
● 1.6㎜×2(BM-S162)
● ○
○
mm x
mm x
○ SD-008RC

REAR

RF ○ ●
RR

-0.5°	3 1H	2-H4 2H-0	1-H3	0-H2 2-H4	3 H1
	3 1H	2-H4 2H-0	1-H3	0-H2 2-H4	3 H1
+0.5°	3 1H	2-H4 2H-0	1-H3	0-H2 2-H4 ●	3 H1

2.5 mm
3 mm
● Z2-300RUD
● Z2-008R
○ ____

● 0°
○ 0.5°
○ 1°

○ 5.0
● 6.0
0.5 mm

○ S ● M ○ L

◆CAMBER ●←→○ 1 °
◆RIDE HEIGHT 23 mm

1 mm
1 mm

○ ____ mm

mm
29 mm

SPRING
● GREEN (YS-A1200)
○ ____

OIL
AE #27.5
○ #1 ○ #2 ○ #3
● 1.6㎜×2(BM-S162)
● ○
○
mm x
mm x

DRIVE

○ # ____ ● #

MOTOR ➪ Racing Performer M2 7.5T Rotor ___ mm
GEAR ➪ Spur 80 T ／ Pinion 22 T : 2.6
BATTERY ➪ Racing Performer Ultra Li-po 7.4V 5000mAh (Shorty)
ESC ● Racing Performer X Series
○ ____

Battery placement

● ○ ○

●5㎜ ×1 ○5㎜ ×___
●10㎜ ×2 ○10㎜ ×___
●20㎜ ×1 ○20㎜ ×___

○YT-RW25
×___

TIRE

FRONT		REAR	
TIRE	➪ PL LP4リブ M3	TIRE	➪ PL ホールショット M4
INSERTS	➪ ノーマル	INSERTS	➪ ノーマル
WHEELS	➪ B2-821HY	WHEELS	➪ B-827

OTHER

● ○ ○ ____

○ ○ ●

COMMENT

Z2-TSSD Z2-TBSD Z2-S2SD Z2-S2LD Z2-670VP
B2-S821A
PLフロントウイング使用
モーターとギヤボックスの間に10g