www.petitrc.com

YZ-2 SETTING SHEET

P040v2
Arn0

DRIVER	Mark A.
DATE	05/05/2015

CIRCUIT RC Plus - Salem, OR

● INDOOR ○ OUTDOOR
○ WET ○ DRY ○ DUSTY ○ SMOOTH ○ BUMPY ○ OTHER
○ LOW TRACTION ● MED TRACTION ○ HIGH TRACTION
○ CLAY ○ GRASS ○ BLUE GROOVE ○ ASTROTURF ○ DIRT ● CARPET ○ WOOD

FRONT

2.0 mm
3 mm
1.0 mm
○ S
○ N
○ Z2-300FU
○ S
○ N
○ Z2-300FL0
○ Z2-300FL5
● B2-300FL(Steel)
19.5 mm

♦ CAMBER ●↔○ 1 °
♦ TOE ○ IN ○ OUT 0 °
mm
○ 0°
○ 2.5°
● 5°
mm
g

SPRING
● YELLOW (YS-A875)
○
OIL
AE 45wt
○ #1 ○ #2 ○ #3
● 2x1.6
0 mm x 0

REAR

RF RR
-0.5° +0.5°
2 mm
♦ CAMBER ●↔○ 2 °
1 mm
○ 0°
○ 0.5°
○ 1°
○ S ● M ○ L
19 mm
mm

SPRING
● GREEN (YS-A1200)
○
OIL
AE 30wt
○ #1 ○ #2 ○ #3
● 2x1.6
1.0 mm x 2

DRIVE

3k

MOTOR	♦ Reedy 7.5	○ Bonded ○ Sintered mm
GEAR	♦ Spur 80 T / Pinion 22 T: 2.6	
BATTERY	♦ SMC 4400	
ESC	○ Racing Performer X Series	
	● Orion R10	

Battery placement
● ○ ○
● YT-RW25

TIRE

FRONT		REAR	
TIRE	♦ Schumacher LP Cut-Stagger Yellow	TIRE	♦ Schumacher Mini-Pin Yellow
INSERTS	♦ None	INSERTS	♦ Schumacher U6734
WHEELS	♦ Schumacher U6801 Pre-mounts	WHEELS	♦ Yokomo

OTHER

○
●
○
○
○

COMMENT

Club racing TQ and win on date of sheet.
Only one of the YT-RW25 weights under the battery is used.
Futaba BLS551 servo.
Ti turnbuckles.
Ti screws on the rear shock tower to car and wing to tower mounts only.
Z2-017G tower and Z2-008FG front arms