

YZ4-F2 DTM3 CAL3

SETTING SHEET Ver.01

CIRCUIT

- INDOOR OUTDOOR
- DIRT ASTROTURF CARPET GLASS WOOD
- WET DRY DUSTY SMOOTH BUMPY
- HARD PACKED CLAY BIUE GROOVE _____
- LOW TRACTION MED TRACTION HIGH TRACTION

DRIVER _____

DATE _____

FRONT

Gull 3mm
 Flat
 Z2-017D(Plastic)

Plastic
 Aluminum

Wide Narrow
 Aluminum
 Plastic

Z2-008F3

S (Plastic)
 B2-300FLS(Steel)
 Z2-300FLO(Aluminum)

CAMBER \leftrightarrow _____ °
 TOE IN OUT _____ °
 RIDE HEIGHT _____ mm

Graphite Hard
 Graphite Hard

4.3
 5.0

01
 02
 03

00°
 2.5°
 5°

A/B
 A'/B'

Wide
 Narrow

Aluminum
 GREEN (YS-A775)

OIL
 # _____
 ϕ 1.6x2

Standard
 2.0 2.2
 mm x _____
 mm x _____

REAR

Z2-018-3 (-3mm)
 Z2-018-2

Plastic
 Z2-300RUM (Aluminum)

Z2-008R3

Standard (CAL2)
 High mount (DTM3)

RF 05 01 RR 05 01

CAMBER \leftrightarrow _____ °
 RIDE HEIGHT _____ mm

4.3
 5.0
 6.0

00
 0.5
 1
 1.5

Aluminum
 GREEN (YS-A1200)

OIL
 # _____
 ϕ 1.7x2 ϕ 1.8x2

Standard
 2.0 2.2
 mm x _____
 mm x _____

DRIVE

OLD
 OLC

03
 02
 01
 00

4-gear
 2-gear

MOTOR \rightarrow _____ Rotor _____ mm
 GEAR \rightarrow Spur T / Pinion T : 2.6
 BATTERY \rightarrow _____
 ESC \rightarrow _____
 SETTING \rightarrow _____

Standard
 Graphite
 Z2-018BMA (Aluminum)

YT-RWS10 x _____
 YT-RW25 x _____

Main chassis
 ODTM3
 OCAL3

Z2-RWT

TIRE

FRONT
 TIRE \rightarrow _____
 INSERTS \rightarrow _____
 WHEELS \rightarrow _____

REAR

TIRE \rightarrow _____
 INSERTS \rightarrow _____
 WHEELS \rightarrow _____

OTHER

Z2-DTM2W (Aero S-Type)
 Z2-CAL2W (LMR27)

COMMENT