

YZ-F1T

SETTING SHEET Ver.01

CIRCUIT

- INDOOR OUTDOOR
 DIRT ASTROTURF CARPET GLASS WOOD
 WET DRY DUSTY SMOOTH BUMPY
 HARD PACKED CLAY BLUE GROOVE _____
 LOW TRACTION MED TRACTION HIGH TRACTION

DRIVER _____

DATE _____

FRONT

Plastic
 Aluminum → ODTM2
 OAL2

CAMBER ← → _____ °

TOE IN OUT _____ °

RIDE HEIGHT _____ mm

Wide Narrow
 Aluminum
 Plastic

OS (Plastic)
 B2-300FLS (Steel)
 Z2-300FLO (Aluminum)
 Z2-300FL5

Graphite
 Z2-415A (Aluminum)
 Graphite
 Hard

0.5mm
 1mm

9.0mm
 9.0mm
 9.0mm

0°
 2.5°
 5°

Aluminum

SPRING
 Standard (YS-FRST)

OIL
 # _____
 φ1.6x2 (BM-S162)

 _____ mm x _____
 _____ mm x _____
 _____ mm x _____

REAR

CAMBER ← → _____ °

RIDE HEIGHT _____ mm

Z2-415R (Plastic)
 Z2-415R00 (Aluminum)

Z2-300RUM (Aluminum)

8.0mm

RF 005 RR 01

S M L

Aluminum

SPRING
 Standard (YS-FRST)

OIL
 # _____
 φ1.7x2 (BM-S172)

 _____ mm x _____
 _____ mm x _____

DRIVE

LD

03
 02
 01
 00

_____ # _____

MOTOR ⇨ _____ Rotor _____ mm

GEAR ⇨ Spur T / Pinion T : 2.6

BATTERY ⇨ _____

ESC YOKOMO BL-PRO4

Standard
 Graphite
 Z2-018BMA (Aluminum)

YT-RW25
 X _____

Z2-002RWT

COMMENT

TIRE

FRONT
 TIRE ⇨ _____
 INSERTS ⇨ _____
 WHEELS ⇨ _____

REAR
 TIRE ⇨ _____
 INSERTS ⇨ _____
 WHEELS ⇨ _____

OTHER

- F2 Body (Standard)

COMMENT