

FINAL POSITION (決賽成績) BEST LAPS (最佳圈數)

CIRCUIT (賽道) PYC

Place (地點) ☐ Indoor (室內) ☒ Outdoor (室外)

Track (場地) ☒ Asphalt (瀝青) ☐ Carpet (地毯)

Traction (抓著力) ☐ High (高) ☒ Medium (中) ☐ Low (低)

Track Condition (場地狀況) ☒ Flat (平坦) ☐ Bumpy (顛簸)

ADVANCE SCH

1/10 SCALE RADIO CONTROL TOURING CAR

SETTING SHEET

FRONT (前方)

Solid Axle (直軸接合器)

☒ Spool (直軸) ☐ Gear (齒式) (油濃度/重量)

Wt / g

Puddy (泥膠)

BELT TENSION ADJUSTMENT ルトデション

☒ UP 上 ☐ LOW 下

Rolling Shim 0 mm

Wheel Hex 5 mm

C Hub

☒ Composite ☐ Aluminum

3 2 1

48 mm

SUS. CENTER GARVITY

FF ☒ 4.5mm ☐ 5.0mm

FR ☒ 4.5mm ☐ 5.0mm

Rolling Shim 0 mm

UP 上 ☐ LOW 下 ☒

0 mm

shock absorber 減震器

Oil (油濃度) # 350

Piston (活塞) 2 ③ 4 Holes 1.1 mm

Spring (彈簧) Blue

Bladder Foam (油壓頂部海綿)

Yes ☐ No ☒

Rebound (彈芯) 25 %

Notes (備註)

Ride Height (離地距) 5 mm

Camber Angle (外傾角) 2 °

Sway Bar (防傾桿) 1.3 mm

Droop (油壓行程) 7.8 mm

Downstop (擺臂止限位) 5.6 mm

Toe Angle (束角) -1 °

REAR (後方)

Gear Diff (齒輪差速器)

☐ Spool (直軸) ☒ Gear (齒式) (油濃度/重量)

3K Wt / g

Puddy (泥膠)

Rolling Shim 0 mm

1.5 mm

1.8 mm

Rolling Shim 0 mm

Wheel Hex 5 mm

SUS. CENTER GARVITY

RF ☒ 4.5mm ☐ 5.0mm

RR ☒ 4.5mm ☐ 5.0mm

BELT TENSION ADJUSTMENT ルトデション

☒ UP 上 ☐ LOW 下

UP 上 ☐ LOW 下 ☒

0 mm

shock absorber 減震器

Oil (油濃度) # 350

Piston (活塞) 2 ③ 4 Holes 1.1 mm

Spring (彈簧) Blue

Bladder Foam (油壓頂部海綿)

Yes ☐ No ☒

Rebound (彈芯) 25 %

Notes (備註)

Ride Height (離地距) 5 mm

Camber Angle (外傾角) 2 °

Sway Bar (防傾桿) 1.4 mm

Droop (油壓行程) 6.8 mm

Downstop (擺臂止限位) 4.6 mm

Toe Angle (束角) 2 °

OTHER (其他)

WIDTH 全幅 188 /mm

WHEEL BASE 259 /mm

WEIGH 1238g

YES ☐ NO ☒

FRONT (前方)	REAR (後方)
Tire (胎皮) Rush	Rush
Compound (胎皮值) 40	40
Insert (胎胎) 039M	039M
Wheel (輪圈) Std	Std
Tire Treatment (胎水) MGV3	MGV3

Spur Gear (大減齒) 83 T 48p	Pinion Gear (摩打齒) 25 T
Motor (馬達) MAGNUM 13.5	Battery (電池) IP 6000 MAH
ESC (電調) HWXR10 Stock	Servo (伺服器) Power HDR12
Body (車殼) 3Racing R35	Wing (風翼) Std
Final Drive Ratio (齒比) (Spur / Pinion x 1.9) : 1 (6.3) : 1	