SETUP SHEET Team Associated RC10TC3 4WD Touring Car FRONT SUSPENSION	Driver: Track/City: Event: Date:
CASTER 0° 2° 4° ANTI-ROLL BAR: None Size: KICKUP 0° 2° -2° TOE-IN ° TOE-OUT ° CAMBER ° RIDE HEIGHT	BODY Composite Alum. SHAFT Std Other: LIMITERS: Inside: Outside: OIL OIL SPRING SHOCK MOUNT & CAMBER LINK Fill in holes used
REAR SUSPENSION ANTI-SQUAT 0° 2° RIDE HEIGHT 4 ANTI-ROLL BAR: None Size: CAMBER: CAMBER: CAMBER: MHEELBASE ADJUSTMENT Short Medium Long	REAR SHOCKS BODY Composite Alum. SHAFT Std Other: LIMITERS: SHOCK MOUNT & CAMBER LINK Outside: CAMBER LINK Fill in holes used PISTON # OIL WT SPRING
FRONT TIRES: Compound: Compound: REAR TIRES: Compound: Compound: Compound: State	BATTERY TYPE: Discrete One-way SPUR/PINION T /T SPRING ESC (oz/gm) Indicate location:
TRACK CONDITIONS SURFACE: Smooth Bumpy TRACTION: Low Med. High COMPOSITION: Concrete Asphalt Carpet Other: NOTES:	RACE COMMENTS MAIN FINISH QUALIFYING. POS NOTES: CAR COMMENTS NOTES: