SETUP SHEET Team Associated RC10TC3 4WD Touring Car FRONT SUSPENSION CASTER 0° 2° 4° ANTI-ROLL KICKUP 0° 2° -2° TOE-IN ° TOE-OUT °	BAR: None Size: ACKERMAN SETTING Std Other: Ball end: Spacer:	Track/City: Event: FRONT SHOCKS BODY Composit	Date: te ☑ Alum. Other: SHOCK MOUNT & CAMBER LINK	
CAMBER° BUMP STEER RIDE HEIGHT		Outside: PISTON # OIL WT SPRING	Fill in holes used	
REAR SUSPENSION ANTI-SQUAT 0° 2° RIE ANTI-ROLL BAR: None Size: TOE-IN 3° Other: CA WHEELBASE ADJUSTMENT FRONT Short Med	°	REAR SHOCKS BODY Composit SHAFT Std C LIMITERS: Inside: C Outside: WT OIL WT SPRING	SHOCK MOUNT & CAMBER LINK Fill in holes used	
OTHER				
	Compound:			
REAR TIRES:				
BATTERY PLACEMENT 🖊 Back 🗌 Fro				
CHASSIS Std Z Carbon Fiber		•		
MOTOR	BRUSH	SPRING		
RADIO	SERVO	ESC	A SECTION OF THE PARTY OF THE P	
BODY TIRE ADDITIVE None SPONSORED BY:	LEAD WEIGHTS _		n: X	
TRACK CONDITIONS		RACE COMMENTS		
SURFACE: Smooth Bumpy		MAIN FINISH _	MAIN FINISH QUALIFYING. POS	
TRACTION: Low Med. High		NOTES:		
COMPOSITION: ☐ Concrete Asphalt ☐ Carpet ☐ Othe	r:	_		
NOTES:		CAR COMMENTS		
		NOTES:		