

NAME _____
 COUNTRY _____
 RACE _____
 TRACK _____

DATE _____ TEMPERATURE AIR / TRACK °C / °C
 ASPHALT ☐ OUTDOOR ☐ INDOOR ☐ CARPET ☐
 TRACK CONDITION BUMPY ☐ FLAT ☐ TECHNICAL ☐ MIXED ☐ FAST ☐
 TRACTION LOW ☐ MEDIUM ☐ HIGH ☐

STEERING BLOCKS
 AT1204-X ☐
 AT1204-ZTX ☐
 OTHER _____

STEERING HUB POSTS
 ST1208-C4S ☐ ST1208-C4AL ☐
 ST1208-C5S ☐ ST1208-C5AL ☐
 ST1208-C6S ☐ ST1208-C6AL ☐
 OTHER _____

SUSPENSION PLATE
 C1205-X ☐
 C1205-ZT ☐
 C1205-X-1.5 ☐
 C1205-6.0 ☐
 OTHER _____

SERVO PLATE
 C1201-X ☐
 C1201-ZT ☐
 C1201 ☐
 OTHER _____

FOAM BUMPER
 P1215 ☐
 OTHER _____

BUMPSTEER SHIMS _____ mm

JOINT SET
 LRC ☐ HRC ☐
 ELRC ☐ EHRC ☐

REAR SRING
 SPR12XR-C0.8 ☐
 SPR12XR-C1.0 ☐
 SPR12XR-C1.2 ☐
 OTHER _____

JOINT SPACER
 FRONT _____ mm
 REAR _____ mm

CAMBER
 0.75 deg ☐
 1.00 deg ☐
 1.25 deg ☐
 1.50 deg ☐
 1.75 deg ☐
 OTHER _____

SIDE SRINGS
 SPR12XS-C0.8 ☐
 SPR12XS-C1.0 ☐
 SPR12XS-C1.2 ☐
 OTHER _____

FRONT HUBS SETUP
 SPR12F C0.7 ☐ C0.9 ☐ C1.1 ☐
 C1.3 ☐ C1.7 ☐

TOP SHIMS _____ mm _____ pcs
BOTTOM SHIMS _____ mm _____ pcs
KINGPIN EXTENSION _____ mm
O-RINGS 0pcs ☐ 1pcs ☐ 2pcs ☐
O-RING TYPE _____
GREASE _____

DAMPER OIL _____
DAMPER STD ☐ HW ☐
OR14V ☐ YES ☐ NO
RIDE HEIGHT SPACERS _____ mm

REAR AXLE
 SSS SPOOL ☐ BALL DIFF ☐ GEAR DIFF ☐
 CS-1 SPOOL ☐ LOOSE ☐ BRAND _____
 CARBON ☐ MEDIUM ☐ OIL _____
 STEEL ☐ TIGHT ☐

FRONT RIDE HEIGHT (FRH)	mm	FRONT DROOP (FD)	mm
REAR RIDE HEIGHT (RRH)	mm	REAR DOWNSTOP (RD)	mm
GAP UNDER DAMPER (GUD)	mm	TRACK WIDTH	
DOWNSTOP NUT GAP (DNG)	mm	FRONT	mm
SPRING ROD HEIGHT (SRH)	mm	REAR	mm

TIRES	FRONT	REAR				
BRAND						
TYPE						
DIAMETER	mm	mm				
ADDITIVE						
			TIME	min	TIME	min

BATTERY		SERVO
BATTERY PLUGS	FRONT ☐ BACK ☐	SERVO SAVER
SERVO POSITION	LEFT ☐ RIGHT ☐	SHIMS ON SERVO SAVER
ESC POSITION	LEFT ☐ RIGHT ☐	TOE OUT
		STEER. TRAVEL IN ° OUT °

MOTOR	TOTAL WEIGHT	g
SPUR PINION ROLLOUT	F/R WEIGHT DISTRIBUTION	%
ESC	RECEIVER	
ESC SETTING	RADIO	
BODY	REAR BODY HEIGHT (SIDE DAMS)	mm
BEST LAP TIME	QUALIF. / FINAL POSITION	/

COMMENTS: