

NAME _____	DATE _____	TEMPERATURE AIR / TRACK °C / °C
COUNTRY _____	ASPHALT ☐ OUTDOOR ☐ INDOOR ☐ CARPET ☐	
RACE _____	TRACK CONDITION BUMPY ☐ FLAT ☐ TECHNICAL ☐ MIXED ☐ FAST ☐	
TRACK _____	TRACTION LOW ☐ MEDIUM ☐ HIGH ☐	

STEERING BLOCKS

AT1204-X ☐

AT1204-ZTX ☐

OTHER _____

STEERING HUB POSTS

ST1208-C4S ☐ ST1208-C4AL ☐

ST1208-C5S ☐ ST1208-C5AL ☐

ST1208-C6S ☐ ST1208-C6AL ☐

OTHER _____

SUSPENSION PLATE

C1205-X ☐

C1205-ZT ☐

C1205-X-1.5 ☐

C1205-6.0 ☐

OTHER _____

SERVO PLATE

C1201-X ☐

C1201-ZT ☐

C1201 ☐

OTHER _____

FOAM BUMPER

P1215 ☐

OTHER _____

BUMPSTEER SHIMS _____ mm

JOINT SET

LRC ☐ HRC ☐

ELRC ☐ EHRC ☐

REAR SPRING

SPR12XR-C0.8 ☐

SPR12XR-C1.0 ☐

SPR12XR-C1.2 ☐

OTHER _____

JOINT SPACER

FRONT _____ mm

REAR _____ mm

CAMBER

0.75 deg ☐

1.00 deg ☐

1.25 deg ☐

1.50 deg ☐

1.75 deg ☐

OTHER _____

DAMPER OIL _____

DAMPER STD ☐ HW ☐

OR14V ☐ YES ☐ NO ☐

RIDE HEIGHT SPACERS _____ mm

SIDE SPRINGS

SPR12XS-C0.8 ☐

SPR12XS-C1.0 ☐

SPR12XS-C1.2 ☐

OTHER _____

FRONT HUBS SETUP

SPR12F C0.7 ☐ C0.9 ☐ C1.1 ☐

 C1.3 ☐ C1.7 ☐

TOP SHIMS _____ mm pcs _____

BOTTOM SHIMS _____ mm pcs _____

KINGPIN EXTENSION _____ mm

O-RINGS 0pcs ☐ 1pcs ☐ 2pcs ☐

O-RING TYPE _____

GREASE _____

REAR AXLE

SSS SPOOL ☐ BALL DIFF ☐ GEAR DIFF ☐

CS-1 SPOOL ☐ LOOSE ☐ BRAND _____

CARBON ☐ MEDIUM ☐ OIL _____

STEEL ☐ TIGHT ☐

FRONT RIDE HEIGHT (FRH)	mm	FRONT DROOP (FD)	mm
REAR RIDE HEIGHT (RRH)	mm	REAR DOWNSTOP (RD)	mm
GAP UNDER DAMPER (GUD)	mm	TRACK WIDTH	
DOWNSTOP NUT GAP (DNG)	mm	FRONT	mm
SPRING ROD HEIGHT (SRH)	mm	REAR	mm

TIRES	FRONT	REAR				
BRAND						
TYPE			FRONT REAR			
DIAMETER	mm	mm				
ADDITIVE			TIME	min	TIME	min

BATTERY		SERVO
BATTERY PLUGS	FRONT ☐ BACK ☐	SERVO SAVER
SERVO POSITION	LEFT ☐ RIGHT ☐	SHIMS ON SERVO SAVER
ESC POSITION	LEFT ☐ RIGHT ☐	TOE OUT
		STEER. TRAVEL IN ° OUT °

MOTOR	TOTAL WEIGHT	g
SPUR PINION ROLLOUT	F/R WEIGHT DISTRIBUTION	%
ESC	RECEIVER	
ESC SETTING	RADIO	
BODY	REAR BODY HEIGHT (SIDE DAMS)	mm
BEST LAP TIME	QUALIF. / FINAL POSITION	/

COMMENTS: