

NAME _____	DATE _____	TEMPERATURE AIR / TRACK °C / °C
COUNTRY _____	ASPHALT ☐ OUTDOOR ☐ INDOOR ☐ CARPET ☐	
RACE _____	TRACK CONDITION BUMPY ☐ FLAT ☐ TECHNICAL ☐ MIXED ☐ FAST ☐	
TRACK _____	TRACTION LOW ☐ MEDIUM ☐ HIGH ☐	

STEERING BLOCKS

AT1204-X ☐

AT1204-ZTX ☐

OTHER _____

STEERING HUB POSTS

ST1208-C4S ☐ ST1208-C4AL ☐

ST1208-C5S ☐ ST1208-C5AL ☐

ST1208-C6S ☐ ST1208-C6AL ☐

OTHER _____

SUSPENSION PLATE

C1205-X ☐

C1205-ZT ☐

C1205-X-1.5 ☐

C1205-6.0 ☐

OTHER _____

SERVO PLATE

C1201-X ☐

C1201-ZT ☐

C1201 ☐

OTHER _____

FOAM BUMPER

P1215 ☐

OTHER _____

BUMPSTEER SHIMS _____ mm

JOINT SET

LRC ☐ HRC ☐

ELRC ☐ EHRC ☐

REAR SRING

SPR12XR-C0.8 ☐

SPR12XR-C1.0 ☐

SPR12XR-C1.2 ☐

OTHER _____

JOINT SPACER

FRONT _____ mm

REAR _____ mm

CAMBER

0.75 deg ☐

1.00 deg ☐

1.25 deg ☐

1.50 deg ☐

1.75 deg ☐

OTHER _____

SIDE SRINGS

SPR12XS-C0.8 ☐

SPR12XS-C1.0 ☐

SPR12XS-C1.2 ☐

OTHER _____

FRONT HUBS SETUP

SPR12F C0.7 ☐ C0.9 ☐ C1.1 ☐

 C1.3 ☐ C1.7 ☐ ☐

DAMPER OIL _____

DAMPER STD ☐ HW ☐

OR14V ☐ YES ☐ NO

RIDE HEIGHT SPACERS _____ mm

SIDE SPRINGS SHIMS _____ mm

SIDE SPRINGS GAP _____ mm

REAR AXLE

SSS SPOOL ☐ BALL DIFF ☐ GEAR DIFF ☐

CS-1 SPOOL ☐ LOOSE ☐ BRAND _____

CARBON ☐ MEDIUM ☐ OIL _____

STEEL ☐ TIGHT ☐

FRONT RIDE HEIGHT (FRH)	mm	FRONT DROOP (FD)	mm
REAR RIDE HEIGHT (RRH)	mm	REAR DOWNSTOP (RD)	mm
GAP UNDER DAMPER (GUD)	mm	TRACK WIDTH	
DOWNSTOP NUT GAP (DNG)	mm		
SPRING ROD HEIGHT (SRH)	mm		
		FRONT	mm
		REAR	mm

TIRES	FRONT	REAR				
BRAND						
TYPE						
DIAMETER	mm	mm				
ADDITIVE						
		FRONT	REAR			
		TIME	min	TIME	min	

BATTERY		SERVO	
BATTERY PLUGS	FRONT ☐ BACK ☐	SERVOSAVER	
SERVO POSITION	LEFT ☐ RIGHT ☐	SHIMS ON SERVOSAVER	mm
ESC POSITION	LEFT ☐ RIGHT ☐	TOE OUT	°
		STEER. TRAVEL	IN ° OUT °

MOTOR	TOTAL WEIGHT	g
SPUR PINION ROLLOUT	F/R WEIGHT DISTRIBUTION	%
ESC	RECEIVER	
ESC SETTING	RADIO	
BODY	REAR BODY HEIGHT (SIDE DAMS)	mm
BEST LAPTIME	QUALIF. / FINAL POSITION	/

COMMENTS: