

NAME **Brandon Clements**  
 COUNTRY \_\_\_\_\_  
 RACE **Speedworld Cup**  
 TRACK **Speedworld**

DATE **9/11/2016** TEMP.°C AIR / TRACK **80°F / °**  
 CARPET  ASPHALT   
 TRACK CONDITION TECHNICAL  MIXED  FAST   
 TRACTION LOW  MEDIUM  HIGH

### FRONT

CASTER FLEX F  R   
 SHIM 0, MM

3 MM  
 3 MM  
 .5 MM  
 AT21S   
 .5 MM

CASTER FLEX F  R   
 SHIM 0, MM

2 MM  
 AT13W   
 3 MM  
 0 MM  
 SC2X6   
 74.6 gF/mm 4.0 MM

CAMBER ANGLE / °	-2			
CASTER ANGLE / °	4			
TOE ANGLE / °	1 Out			
RIDE HEIGHT / MM	5.2			
DOWNSTOP / MM	5.6			
UPSTOP / MM				
STABILIZER Ø / MM	1.1			
LOW ARM C04AL <input type="checkbox"/>	C04M+.5 <input type="checkbox"/>			
STEERING ARM STD <input type="checkbox"/>	AM14A <input checked="" type="checkbox"/>			
WHEEL SPACER / MM				
FRONT DRIVE GD3 <input type="checkbox"/>	SPOOL <input checked="" type="checkbox"/>	GD2B <input type="checkbox"/>	LOW <input type="checkbox"/>	HIGH <input checked="" type="checkbox"/>
DIFF OIL	DIFF WASHERS			
DOGBONE DRIVE ST17-1 <input type="checkbox"/>	ST11 <input checked="" type="checkbox"/>	ST12 <input type="checkbox"/>	BB <input type="checkbox"/>	ST02 <input type="checkbox"/>

OIL 550cst  
 SHOCKS SET  
 ROTOR STD  S   
 SPRING STD  S   
 DAMPER D2.1   
 ACTION SYM.  ASYM.   
 SRS/RHS ARR. I  II

### REAR

CASTER FLEX F  R   
 SHIM 0, MM

2 MM  
 AT13W   
 2.75 MM  
 0 MM  
 SC2X6   
 102.6 gF/mm 3.6 MM

1.75 MM  
 2.75 MM  
 .5 MM  
 AT21S   
 .5 MM

CAMBER ANGLE / °	-2			
CASTER ANGLE / °	4 forward			
TOE ANGLE / °	2			
RIDE HEIGHT / MM	5.4			
DOWNSTOP / MM	4.4			
UPSTOP / MM				
STABILIZER Ø / MM	1.2			
LOW ARM C04AL <input type="checkbox"/>	C04M <input type="checkbox"/>			
STEERING ARM STD <input checked="" type="checkbox"/>				
WHEEL SPACER / MM				
REAR DRIVE GD3R <input type="checkbox"/>	GD2B <input type="checkbox"/>	LOW <input type="checkbox"/>	HIGH <input checked="" type="checkbox"/>	
DIFF OIL 10k	DIFF WASHERS			
DOGBONE DRIVE ST11 <input checked="" type="checkbox"/>	ST12 <input type="checkbox"/>	BB <input type="checkbox"/>	ST17-1 <input type="checkbox"/>	EVD <input type="checkbox"/>

OIL 550cst  
 SHOCKS SET  
 ROTOR STD  S   
 SPRING STD  S   
 DAMPER D2.1   
 ACTION SYM.  ASYM.   
 SRS/RHS ARR. I  II

### FRAME FLEX SETTING

FRONT BATTERY CONNECTORS 15g  
 REAR 10g  
 C25   
 CHASSIS STIFFENER and MOTOR MOUNT SCREWS 65g  
 ADDITIONAL WEIGHTS 15g 10g

LOWER DECK C01B-2.25  
 CHASSIS STIFFENER AM110  AM115  ST130   
 C26  C26   
 TOP DECK CUTS  
 ST09 TOP DECK C27  VTD   ST09   
 Std  Cut  AM98 AT63  AT63  C38  AM98 Std  Cut

### TIRES

FRONT	REAR
BRAND <b>Solaris</b>	<b>40J</b>
INSERTS	
WHEELS	
ADDITIVE <b>MG Red</b>	

MOTOR LATERAL SHIFT / MM \_\_\_\_\_  
 ACKERMANN SHIMS / MM **2mm**  
 DRIVE RATIO **7.7**  
 SPUR **114** PINION **28**  
 BODY **LT CR LW**  
 WING **PF high downforce**

MOTOR **LRP X20 4.5**  
 SERVO **Futaba BLS551**  
 STEER TRAVEL **Max**  
 ESC **LRP Flow**  
 BATTERY **Team powers 5800 LCG**  
 RECEIVER **Sanwa**

ESC SETTING  
 BEST LAP TIME **12.2** QUALIF. / FINAL POSITION **1 / 1**  
 CONTACT \_\_\_\_\_

**AM06W**  
**AM19-4 in rear**  
**Note front SRS/RHS ARR 2**