

NAME **Chris Mitchell**  
 COUNTRY **Australia**  
 RACE **2020 Spring Cup**  
 TRACK **West Coast Model RC - Blue Layout**

DATE **13/09/2020** TEMP. °C AIR / TRACK **24 /**  
 ASPHALT  OUTDOOR  INDOOR  CARPET   
 TRACK CONDITION TECHNICAL  MIXED  FAST   
 TRACTION LOW  MEDIUM  HIGH

### FRONT

3.25MM  
 AM19-FX-US  
 Extra Long TL  
 AM19-2  
 3.25MM  
 AT21  
 2.5MM  
 AT21  
 3.0MM  
 0.5MM  
 AT13W  
 4.5MM  
 0MM  
 SC2X6

CAMBER ANGLE / ° **2**  
 CASTER ANGLE / ° **4**  
 TOE ANGLE / ° **1.5 (out)**  
 RIDE HEIGHT / MM **5.6**  
 DOWNSTOP / MM **6.0**  
 UPWNSTOP / MM **-**  
 STABILIZER Ø / MM **1.0**  
 LOW ARM C04M1+9.0   
 STEER. ARM AM14LS   
 WHEEL SPACER / MM  
 FRONT DRIVE SPOOL  GB2B  LOW  HIGH   
 DIFF. OIL  
 DIFF WASHERS  
 WHEELHUB AM06WL

**67.2GF/MM** **2.2MM**  
 OIL **550cst**  
**1.0MM**  
**SHOCKS SET**  
 ROTOR STD   
 SPRING STD  S   
 DAMPER D2.2  ADC   
 SRS/RHS ARR. I  II   
 PSS SETUP 25%  15%

### REAR

2.25MM  
 AM19-FX-US  
 Extra Long TL  
 AM19-2  
 2.25MM  
 AT21  
 3.5MM  
 AT21  
 3.5MM  
 0.5MM  
 AT13W  
 4.5MM  
 0MM  
 SC2X6

CAMBER ANGLE / ° **2**  
 CASTER ANGLE / ° **4 (Short)**  
 TOE ANGLE / ° **3**  
 RIDE HEIGHT / MM **6.0**  
 DOWNSTOP / MM **4.4**  
 UPWNSTOP / MM **-**  
 STABILIZER Ø / MM **1.1**  
 LOW ARM C04M1+8.0   
 STEER. ARM AM23-1   
 WHEEL SPACER / MM  
 REAR DRIVE GB2B  LOW  HIGH   
 DIFF. OIL **7500**  
 DIFF WASHERS **SH5x7x0.4 - OR05V oring**  
 WHEELHUB AM06WL

**108.4GF/MM** **3.0MM**  
 OIL **550cst**  
**3.0MM**  
**SHOCKS SET**  
 ROTOR STD   
 SPRING STD  S   
 DAMPER D2.2  ADC   
 SRS/RHS ARR. I  II   
 PSS SETUP 25%  15%

### CHASSIS FLEX AND WEIGHT SETTINGS

BSSX STEERING   
 11g  g  g  g  
 10g  1 2 3 4 5  19g  
 MOTORMOUNT SCREWS  
 11g  20g  AM105 SCREWS  
 LOWER DECK C01B-X-MM2  C01B-X-MMA   
 C26  C26   
 FRONT REAR  
 TOP DECK CUTS  
 FRONT TOP DECK C127  C127S  REAR TOP DECK C127  C127S

### TIRES

**Volante**

INSERTS  
 WHEELS  
 ADDITIVE **ATS** TIME - FR **10** RR **10**  
 TOTAL WEIGHT **1343** WEIGHT DISTRIBUTION F **50** % R **50** %  
 NOTES:  
 MOTOR LATERAL SHIFT / MM **0** ACKERMANN POSITION **Max Forward**  
 MOTOR **R1 V21 13.5t-50deg timing** SERVO **R1 Wurks**  
 SPUR **96** PINION **42** RATIO **4.34** STEER TRAVEL IN **26deg** OUT  
 BODY **Zoo Baybee 0.7** BATTERY **R1 6000mAh**  
 WING **Baybee STD** RECEIVER  
 ESC **R1 Digital 3** RADIO  
 ESC SETTING **Max Punch, Max Power, 70% Start power, 2k freq**  
 BEST LAP TIME **15.2** QUALIF./FINAL POSITION **1 / 1**

**RCMaker Slimflex Chassis, Centraflex 1.6mm Top Decks, GeoCarbon Steering Arms, Brass AFEP, Brass Floating ESC Plate, Brass Weights Front (in), Under Bellcrank & Behind MM AM42-20. AT15 & AT22M.**  
**\*IMPORTANT\* SuperExtraLong Top Links (Used At25-44 Turnbuckles)**