


DATE		TEMP. °C	AIR / TRACK	/
TRACK SURFACE			ASPHALT ☐	CARPET ☐
TRACK LAYOUT	TECHNICAL ☐		MIXED ☐	FAST ☐
TRACTION		LOW ☐	MEDIUM ☐	HIGH ☐

REAR






Diagram of a shock absorber assembly with adjustment points labeled MM, GF/MM, OIL, and a pressure gauge.

ST205 ☐

ST05-R ☐

SHOCKS SETUP

DAMPER D4 ☐

ROTOR 2 HOLES ☐

SPRING STD ☐ S ☐


SRS/RHS ARR. I ☐ II ☐

PSS SETUP 30% ☐ 25% ☐ 15% ☐

DAMPING LINEAR ☐ P1 ☐ P2 ☐

DAMPER SPACER / MM

C45 YES ☐ NO ☐



CAMBER ANGLE / °

CASTER ANGLE / °

TOE ANGLE / °

RIDE HEIGHT / MM

DOWNSTOP / MM

UPSTOP / MM

ANTI-ROLL BAR Ø / MM

ARB STIFFENER 1/4 1/2 3/4 1

LOWER ARM EXTENSION / MM

STEER. ARM AM23-1

2ND SPRING SPR-P2 P1

WHEEL SPACER / MM

DRIVE DIFF

DRIVE POSITION DOWN UP +1

DIFF OIL DIFF SHIMS

SHOCKS SETUP

DAMPER D4

ROTOR 2 HOLES

SPRING STD S



SRS/RHS ARR. I II

PSS SETUP 30% 25% 15%

DAMPING LINEAR P1 P2

DAMPER SPACER / MM

C45 YES NO



SURFACE TO WING

