

Camber:

Caster Upper Arm Pos.: mm:

Upper Support Level

Shock Tower

Down Stop:

Track Width:

Height:

Toe out:

Note for Body Type & C.:

Caster:

Position:

WEIGHTS:

Measure:

Position: ○○○

Shock Tower

Centerring Position

Camber:

Rear Hub Spacer:

Position: ○○

Position: ○○○

Down Stop:

Track Width:

Height:

Inserts:

OUT

IN

Inserts: IN OUT

Toe in:

Position: ○

WEIGHTS:

DRIVER:

DATE:

TRACK:

SURFACE: ☐ Smooth ☐ Rough

TRACTION: ☐ Low ☐ Medium ☐ High

LAYOUT: ☐ Slow ☐ Mixed ☐ Fast

POWERTRAIN

TYPE

FUEL

GLOW PLUG

PIPE / MANIFOLD

CLUTCH SETTINGS

SHOE/BELL

CLEARANCE (mm)

AXIAL PLAY (mm)

SPRING

TENSION (mm)

TYRES

FRONT		BRAND	REAR	
LEFT	RIGHT		LEFT	RIGHT
		SHORE		
		DIAMETER START		
		DIAMETER STOP		

SHOCK ABSORBERS

FRONT	REAR
PISTON	PISTON
OIL	OIL
SPRING	SPRING

FRONT - ANTI ROLL BAR

2,1 ☐ 2,3 ☐ 2,5 ☐ opt:

REAR - ANTI ROLL BAR

2,6 ☐ 2,8 ☐ 3,0 ☐ opt:

SERVO SAVER POSITION

mm

FRONT

REAR

PINION 1ST: ☐ 18T ☐ 19T ☐ 20T

PINION 2ND: ☐ 23T ☐ 24T ☐ 25T

SPUR 1ST: ☐ 59T ☐ 60T ☐ 61T

SPUR 2ND: ☐ 55T ☐ 56T ☐ 57T