

CFR1 SETUP SHEET

NAME: _____ COMPOSITION: ☐ ASPHALT ☐ CARPET
DATE: _____ TRACTION: ☐ LOW ☐ MEDIUM ☐ HIGH
RACE: _____ LAYOUT: ☐ TECHNICAL ☐ MIXED ☐ FAST
TRACK: _____ SURFACE: ☐ SMOOTH ☐ BUMPY
COUNTRY: _____

TEMPERATURE
AIR: _____
TRACK: _____
TYRES: _____

CASTOR SETTING			
0.0mm	☐	0.5° / 2.5mm	☐ 8.0°
0.5mm	☐	2.0° / 3.0mm	☐ 9.5°
1.0mm	☐	3.5° / 3.5mm	☐ 11.0°
1.5mm	☐	5.0° / 4.0mm	☐ 12.5°
2.0mm	☐	6.5° / 4.5mm	☐ 14.0°

FRONT

UPPER ARM WIDTH ☐ STD ☐ _____
LOWER ARM WIDTH ☐ STD ☐ _____

SPACER: _____ mm
SPACER: _____ mm
SPACER: _____ mm
SPRING: _____
LUBE: _____
SPACER: _____ mm
SPACER: _____ mm
RIDE HEIGHT: _____ mm
DROOP: _____ mm
FROM RIDE HEIGHT

FRONT WING: _____ TOE: _____
EXTRA FLAP: _____ STEERING LOCK: _____

AXLE SPACER: _____ mm
FRONT WIDTH: _____ mm

CAMBER SETTING
A-DIRECTION: 0.0mm ☐ -1.5°
0.25mm ☐ -0.75° / 0.5mm ☐ 0.0°
B-DIRECTION: 0.0mm ☐ -3.0°
0.25mm ☐ -2.25° / 0.5mm ☐ -1.5°
0.75mm ☐ -0.75° / 1.0mm ☐ 0.0°

REAR

REAR WING: _____
REAR WING HEIGHT
SPACER: _____ mm
RIDE HEIGHT: _____ mm

SPACER: _____ mm
REAR WIDTH: _____ mm
SPACER: _____ mm
REAR WING SPACER: _____ mm

SPACER: _____ mm
DIFFERENTIAL BALL ☐
SETTING: _____
GEAR ☐
OIL: _____
SPOOL ☐

CENTER

LUBE: _____
SPRING: _____
GAP: _____ mm
GAP: _____ mm
SPACER: _____ mm
SPACER: _____ mm
SPACER: _____ mm
SPACER: _____ mm
OVERALL SHOCK LENGTH: _____ mm

SPACER: _____ mm
PRELOAD: _____ mm
SPACER: _____ mm
SPRING: _____
OIL: _____
PISTON: _____
REBOUND: _____

SIDE TOP DESK: _____
RIDE HEIGHT: _____ mm
DROOP: _____ mm
FROM RIDE HEIGHT
CHASSIS: _____ mm

ELECTRONICS

SERVO: _____
ESC: _____
BATTERY: _____ / _____ C
RECEIVER: _____
MOTOR: _____
TIMING: _____
ROTOR: _____
SPUR: _____ PINION: _____
RATIO: _____

TIRES

FRONT: _____
REAR: _____
ADDITIVE: _____
TIME: _____
WARMER: _____ DEG _____ MIN

IN FRONT OUT IN REAR OUT

NOTES