

### Track Conditions

Composition: Asphalt Carpet Other:

Traction: Low High

Surface: Smooth

Layout: Open Both Tight

Bumpy

Indoor

Outdoor

### Front End

Front spring:

Front ride height:

Front camber:

Toe angle:

King pin length:

Front axle: Trailing Inline

Front track width:

#### **Pro-Strut front end**

Caster Shim position: 0 forward 2 forward

1 forward 3 forward

Dynamic caster block: 0° 5° 10°

#### **Ride height spacer**

Coarse: 3mm 4mm 5mm

Fine: 0.25mm white 0.5mm yellow 0.75 orange

#### **Option Parts**

3277 Graphite brace

Dual Arm Long Short

Pin Brace

### Front tires

Brand compound:

Diameter (mm):

Traction compound:

Time & surface:

### Rear End / Center

Shock oil:

Center spring:

Preload:

Ball stud – front:

– rear:

Damper tube lube:

Side spring:

Preload:

Roll center:

Ride height – mid:

rear:

Pod droop:

Rear track width:

Shims – left:

right:


Pod plane – unloaded :

loaded:

Battery position:

forward

rearward



### Rear tires

Brand compound:

Diameter (mm):

Traction compound:

Time & surface:

### Body & Electronics

Body:

Body position:

Wing / Spoiler: yes no

Receiver:

Servo:

Battery:

Motor:

Gearing:

ESC:

ESC settings:

### Comments