

IF14-2 SET-UP SHEET

NAME	
DATE	
TRACK	
EVENT	

QUAL. POSITION	FINAL POSITION	BEST LAP	RACE LENGTH
		sec	min

TEMPERATURE AIR	TEMPERATURE TRACK

TRACK	
TRACK SURFACE	☐ ASPHALT ☐ CARPET
TRACK LAYOUT	☐ TECHNICAL ☐ MIXED ☐ FAST
TRACTION	☐ LOW ☐ MEDIUM ☐ HIGH

FRONT	TRANSMISSION	REAR
☐ SOLID AXLE		
☐ GEAR DIFFERENTIAL	☐ GEAR DIFFERENTIAL	
OIL	OIL	
PINION GEAR	SPUR GEAR	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
☐ HARD ☐ SOFT	MEMBRANE	☐ HARD ☐ SOFT
	SPRINGS	
	OIL	
	REBOUND (%)	
☐ 3 HOLES ☐ 1.1mm	PISTONS	☐ 3 HOLES ☐ 1.1mm
☐ 4 HOLES ☐ 1.2mm		☐ 4 HOLES ☐ 1.2mm
	LENGTH	
	OTHER	

FRONT	TIRES	REAR
	TIRES	
	INSERTS	
	WHEELS	
	ADDITIVE	
	ADDITIVE TIMING	

MOTOR	TIMING
ESC	BATTERIES
BODY	WING

COMMENTS

WHEELBASE SHIM	BALANCE	TOP DECK	MAIN CHASSIS	BALANCE	WHEELBASE SHIM
FR	g	☐ STANDARD(2mm) ☐ 1.6mm	☐ STANDARD(2.25mm) ☐ ALUMINUM	g	RR
mm					mm

DIFF. POSITION	TOP DECK FLEX	BALANCE	DIFF. POSITION
☐ UP ☐ DOWN ☐ STANDARD ☐ ALUMINUM	☒ SCREW USED ☐ SCREW NOT USED	g	☐ UP ☐ DOWN ☐ STANDARD ☐ ALUMINUM
WIDTH	SHIMS UNDER TOP DECK		WIDTH
mm	☐ YES ☐ NO		mm
	mm		

TOP DECK FLEX	BALANCE	WIDTH
☐ STIFF ☐ MEDIUM ☐ NO POST	g	mm

FRONT	REAR
TOE OUT	TOE IN
deg.	deg.
BUMP STEER SHIM	ANTI-ROLL BAR
mm	mm
UNDER SHOCK SHIMS	UNDER SHOCK SHIMS
LOWER	LOWER
mm	mm
UPPER	UPPER
mm	mm
CHASSIS STIFFENER	MOTOR MOUNT, REAR STIFFENER FLEX
☐ YES ☐ NO	☒ SCREW USED ☐ SCREW NOT USED
STEERING PLATE	SERVO HONE
☐ 8.0mm ☐ 8.5mm ☐ 9.0mm	☐ STANDARD ☐ ALUMINUM ☐ 17mm ☐ 18mm ☐ 19mm ☐ 20mm

FRONT	SHOCK MOUNT BUSHING	SHIM	SHOCK MOUNT BUSHING	SHIM	STEERING BLOCK	FRONT ARM
UPPER ARM MOUNT SPACER	☐ 0 ☐ IN ☐ OUT	mm	☐ 0 ☐ IN ☐ OUT	mm	☐ GRAPHITE ☐ HARD	☐ GRAPHITE ☐ HARD
mm	☐ 0.4 ☐ 0.8 ☐ 1.2		☐ 0.4 ☐ 0.8 ☐ 1.2			
ANTI-ROLL BAR					WHEEL HUB	CAMBER ANGLE
mm					☐ STANDARD (5.0) ☐ 4.5 ☐ 4.25	deg.
SUS. BLOCK					WHEEL SHIM	RIDE HEIGHT
FF ☐ 4.5 ☐ 4.5					mm	mm
FR ☐ 6.0 ☐ 6.0						
SUS. BLOCK SPACER	SUS. HOLDER SPACER	ECCENTRIC BUSHING	SUS. PLATE		DOWNSTOP	DROOP (Downstop +3.5mm)
FF mm	FF mm	FF ☐ 0.5 ☐ 1 ☐ 0.5 ☐ 1	☐ 0 ☐ IN ☐ OUT		mm	mm
FR mm	FR mm	FR ☐ 0.5 ☐ 1 ☐ 0.5 ☐ 1	☐ 0.4 ☐ 0.8 ☐ 1.2			
					OTHER	

PRS SYSTEM

Passive Rear Steering

C-HUB	SHIM	SHIM
☐ ALUMINUM	mm	mm
STEERING BLOCK		
☐ GRAPHITE ☐ HARD		
WHEEL HUB		
☐ STANDARD (5.0) ☐ 4.5 ☐ 4.25		
WHEEL SHIM		
mm		

REAR	SHOCK MOUNT BUSHING	SHIM	SHOCK MOUNT BUSHING	SHIM	REAR UPRIGHT	REAR ARM
UPPER ARM MOUNT SPACER	☐ 0 ☐ IN ☐ OUT	mm	☐ 0 ☐ IN ☐ OUT	mm	☐ GRAPHITE ☐ HARD	☐ GRAPHITE ☐ HARD
mm	☐ 0.4 ☐ 0.8 ☐ 1.2		☐ 0.4 ☐ 0.8 ☐ 1.2			
ANTI-ROLL BAR					WHEEL HUB	CAMBER ANGLE
mm					☐ STANDARD (5.0) ☐ 4.5 ☐ 4.25	deg.
SUS. BLOCK					WHEEL SHIM	RIDE HEIGHT
RF ☐ 0.0 ☐ 4.5					mm	mm
RR ☐ 4.5 ☐ 6.0						
SUS. BLOCK SPACER	SUS. HOLDER SPACER	ECCENTRIC BUSHING	SUS. PLATE		DOWNSTOP	DROOP (Downstop +3.5mm)
RF mm	RF mm	RF ☐ 0.5 ☐ 1 ☐ 0.5 ☐ 1	☐ 0 ☐ IN ☐ OUT		mm	mm
RR mm	RR mm	RR ☐ 0.5 ☐ 1 ☐ 0.5 ☐ 1	☐ 0.4 ☐ 0.8 ☐ 1.2			
					OTHER	