

SETUP SHEET
 FLY-TECH

EVENT			
TRACK			
NAME	DATE		

QUALIFY	FINAL	
BEST LAP	LAP / TIME	/
TEMP. AIR	TEMP. TRACK	

TRACK			
SURFACE	☐ ASPHALT	☐ CARPET	
LAYOUT	☐ TECHNICAL	☐ MIXED	☐ FAST
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH

TRANSMISSION	FRONT	REAR
DIFF OIL	☐ SOLID AXLE	
PULLEY	☐ 38/20T	☐ 40/22T
	☐ STD.	☐ LOW FRICTION
PINION	T	FDR
	SPUR	

SHOCKS	FRONT	REAR
MEMBRANE	☐ HARD ☐ SOFT ☐ SOFT V2	☐ HARD ☐ SOFT ☐ SOFT V2
SPRINGS		
OIL		
REBOUND (%)		
PISTONS		
LENGTH	mm	mm
STABILIZER	mm	mm

TIRES	FRONT	REAR
TIRES		
ADDITIVE		
TIMING		
WARMERS	Temp.	Timing
	Temp.	Timing

MOTOR & BATTERIES	
MOTOR	TIMING
ESC	BATTERY

WEIGHT BALANCE	
WEIGHT	g
BALANCE	FRONT % REAR %

BODY	
BODY	WING

BODY POSITION	
Dimension from body post to windows bottom line	mm
Dimension from body post to upper holder	mm
SIDE PLATE	☐ YES ☐ NO
Dimension from edge to surface	mm

TOP DECK	
☐ 1.6mm ☐ 2.0mm	☐ 1.6mm ☐ 2.0mm
☐ Screws	☐ Shims
☐ TOP DECK CUTTING	

COMMENTS	
----------	--

FRONT	REAR
CASTER	TOE GAIN
deg.	mm
BUMP STEER	CASTER
mm	deg.
SHIM	
mm	
HEIGHT	
mm	
FF SHIM	RF SHIM
mm	mm
RIDE HEIGHT	RIDE HEIGHT
mm	mm
FR SHIM	RR SHIM
mm	mm
SERVO HORN	
☐ ALU	
☐ STD.	

FRONT	
CAMBER	SHIM
deg.	mm
BODY STOP	SHOCK SHIM
☐ YES ☐ NO	mm
SHIM	SHIM
mm	mm
FR SHIM	FR SHIM
mm	mm
BULK BRACE	SHOCK SHIM
☐ YES ☐ NO	mm
SHOCK SHIM	SHIM
mm	mm
FRONT HUB	
☐ GRAPHITE	
☐ HARD	
DROOP	
mm	
Set with shocks	
Set without shocks	
SHIM	
mm	

REAR	
CAMBER	SHIM
deg.	mm
BODY POST	SHOCK SHIM
☐ VERTICAL	mm
☐ HORIZONTAL	mm
SHIM	SHIM
mm	mm
FR SHIM	FR SHIM
mm	mm
BULK BRACE	SHOCK SHIM
☐ YES ☐ NO	mm
SHOCK SHIM	SHIM
mm	mm
REAR HUB	
☐ GRAPHITE	
☐ HARD	
DROOP	
mm	
Set with shocks	
Set without shocks	
SHIM	
mm	

TOE	ACKERMANN	TOE IN
deg.	mm	deg.
DIFF POSITION	CENTER WEIGHT	DIFF POSITION
☐ UP	☐ 14g ☐ 10g	☐ UP
☐ DOWN	g	☐ DOWN
HUB	STEER PLATE	HUB
☐ +0.5mm	☐ 8.5mm	☐ +0.5mm
☐ STD.	☐ 8.0mm(STD)	☐ STD.
☐ -0.5mm	SHIM	☐ -0.5mm
SHIM	mm	SHIM
mm		mm

STEER. LOCK	FRONT BRACE	MOTOR MOUNT	REAR BRACE
deg.	☐ YES ☐ NO		☐ YES ☐ NO
FRONT ARMS	CHASSIS		REAR ARMS
☐ HARD	☐ GRAPHITE		☐ HARD
☐ STD.	☐ ALU 2.0mm		☐ STD.