

IF14 SPECIALE SET-UP SHEET

IF14 SPECIALE

EVENT			
TRACK			
NAME			DATE

QUAL. POSITION	FINAL POSITION	
BEST LAP	LAP / TIME	
TEMP. AIR	TEMP. TRACK	

TRACK

TRACK SURFACE	☐ ASPHALT	☐ CARPET	
TRACK LAYOUT	☐ TECHNICAL	☐ MIXED	☐ FAST
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH

TRANSMISSION

FRONT	REAR
GEAR DIFF OIL	☐ SOLID AXLE
PULLEY	☐ 38/20T ☐ 40/22T ☐ STD. ☐ LOW FRICTION
PINION	SPUR GEAR
FINAL DRIVE RATIO	

SHOCKS

FRONT	REAR
MEMBRANE	☐ HARD ☐ SOFT ☐ SOFT V2
SPRINGS	☐ HARD ☐ SOFT ☐ SOFT V2
OIL	
REBOUND (%)	
PISTONS	☐ 1.1mm ☐ 1.2mm ☐ 1.1mm ☐ 1.2mm
LENGTH	mm
STABILIZER	mm

TIRES

FRONT	REAR
TIRES	
ADDITIVE	
ADDITIVE TIMING	
TIRE WARMERS	Temp. Timing Temp. Timing

MOTOR & BATTERIES

MOTOR	TIMING
ESC	BATTERIES

WEIGHT BALANCE

TOTAL WEIGHT	g	WEIGHT BALANCE	FRONT	%	REAR	%
--------------	---	----------------	-------	---	------	---

BODY

BODY	WING
------	------

BODY POSITION

Dimension from body post to windows bottom line

Dimension from body post to upper holder

WING SIDE PLATE ☐ YES ☐ NO

Dimension from edge to surface

TOP DECK

☐ 1.6mm ☐ 2.0mm ☐ 1.6mm ☐ 2.0mm	Screws	Shims
TOP DECK CUTTING		

COMMENTS

FRONT

FRONT CASTER deg.

BUMP STEER mm

SHIM mm

HEIGHT mm

FF/SHIM mm

RIDE HEIGHT mm

FR/SHIM mm

SERVO HORN ☐ ALU ☐ STD.

REAR

TOE GAIN mm

REAR CASTER deg.

RF/SHIM mm

RIDE HEIGHT mm

RR/SHIM mm

FRONT

FRONT CAMBER deg.

BODY STOP ☐ YES ☐ NO

SHIM FF mm

SHIM FR mm

SHOCK SHIM mm

SHIM mm

FRONT HUB ☐ GRAPHITE ☐ HARD

REINFORCE BRACE ☐ YES ☐ NO

BULK BRACE ☐ YES ☐ NO

SHOCK SHIM mm

SHIM mm

DROOP AXLE HEIGHT mm

SHIM ☐ Set with shocks ☐ Set without shocks

REAR

REAR CAMBER deg.

BODY POST ☐ VERTICAL ☐ HORIZONTAL

SHIM FF mm

SHIM FR mm

SHOCK SHIM mm

SHIM mm

REAR HUB ☐ GRAPHITE ☐ HARD

REINFORCE BRACE ☐ YES ☐ NO

BULK BRACE ☐ YES ☐ NO

SHOCK SHIM mm

SHIM mm

DROOP AXLE HEIGHT mm

SHIM ☐ Set with shocks ☐ Set without shocks

FRONT TOE OUT deg.

ACKERMANN mm

REAR TOE IN deg.

CENTER WEIGHT ☐ 14g ☐ 10g

DIFF POSITION ☐ UP ☐ DOWN

BEARING HOLDER ☐ 0.75mm ☐ 0.5mm(STD) ☐ 0.25mm

WHEEL HUB ☐ +0.5mm ☐ STD. ☐ -0.5mm

STEERING PLATE ☐ 8.5mm ☐ 8.0mm(STD)

SHIM mm

WHEEL HUB ☐ +0.5mm ☐ STD. ☐ -0.5mm

SHIM mm

STEER. LOCK deg.

CHASSIS BRACE ☐ YES ☐ NO

MOTOR MOUNT

CHASSIS ☐ GRAPHITE ☐ ALU 2.0mm

FRONT ARMS ☐ HARD ☐ STD.

REAR ARMS ☐ HARD ☐ STD.