

NAME	
DATE	
TRACK	
EVENT	
TRACTION	
SURFACE	

PINION	TRANSMISSION	SPUR
☐ 15T ☐ 16T ☐ 17T	☐ 1ST ☐ 2ND	☐ 58T ☐ 59T ☐ 53T ☐ 54T
☐ 20T ☐ 21T ☐ 22T		

SIDE PULLEY
☐ 25T(STD) ☐ 26T(OPT)

FRONT	SHOCKS	REAR
☐ SHORT ☐ STD	TYPE	☐ SHORT ☐ STD
	SPRINGS	
	OIL	
☐ STD ☐ OPTION	O-RING	☐ STD ☐ OPTION
	PISTONS	

FRONT	DIFFERENTIAL	REAR
☐ UP ☐ STD	☐ DIFF ☐ G228 ☐ ADJUSTABLE ☐ ONE WAY	☐ UP ☐ STD

FRONT	ANTI-ROLL BAR	REAR
	mm	mm

FRONT	RIDE HEIGHT	REAR
	mm	mm

FRONT	TRACK WIDTH	REAR
	mm	mm

TYRES		CONTROLLED
LEFT	RIGHT	☐
FRONT	REAR	
mm	mm	

FRONT	WHEEL PLATE	REAR
☐ YES ☐ NO		☐ YES ☐ NO

HEX HUB	U (UNIVERSAL) / D (DRIVE SHAFT)
☐ STD ☐ OPT ☐ OPT (LARGE)	FRONT REAR
	☐ 90° U(OPT) ☐ 0° D(OPT) ☐ 0° U(STD) ☐ 0° U(50mm)

AERODYNAMICS	
BODY	CENTERING POST
	mm
BODY POSITION	mm
REAR SPOILER	mm

BODY MOUNT	
IN MID OUT	LOW HIGH
	mm

SHOCK TOWER	
G185 (STD)	G215 (SHORT)
CASTER	mm
SPACER	mm
TOE OUT	deg.
KNUCKLE PLATE POSITION	
UPPER SHIM	mm
UPPER POSITION	
CAMBER	deg.
DOWNSTOP	mm

SHOCK TOWER	
G132 (STD)	G156 (SHORT)
WHEELBASE SHIM	mm
SPACER	mm
TOE IN	deg.
SUSP. BLOCK POSITION	
☐ STANDARD ☐ WIDE (G076/G077)	
SUSPENSION COVER	
☐ NO ☐ STANDARD ☐ HARD ☐ CARBON	
SCREW POINT	
CAMBER	deg.
UPPER POSITION	☐ IN ☐ OUT
DOWNSTOP	mm

SERVO SAVER	
☐ 9 ☐ 10 ☐ 11	POSITION
☐ STD ☐ AL	
UPPER STIFFENER	☐ YES ☐ NO
CENTER BULK	☐ STD ☐ AL

CENTER STIFFENER	
☐ YES ☐ NO	☐ YES ☐ NO
REAR CHASSIS STIFFENER	
☐ YES ☐ NO	

WEIGHT	
28g 20g 14g 9.5g	
1	☐
2	☐
3	☐
4	☐
5	☐
6	☐
7	☐
8	☐