

IF18-3 SET-UP SHEET ver.1.0

NAME	DJ Apolaro
DATE	
TRACK	Medium traction
EVENT	

PINION	TRANSMISSION	SPUR	SHAFT
☐ 18T ☒ 19T ☐ 20T	☐ 1ST ☒ 60T ☒ 61T ☐ 62T	☐ 6mm	
☐ 23T ☒ 24T ☐ 25T	☐ 2ND ☒ 56T ☒ 57T ☐ 58T	☐ 8mm	

FRONT	SHOCKS	REAR
R8011	SPRINGS	R8017
# 600	OIL	# 600
☒ STD ☐ OPTION	☒ STD ☐ OPTION	
☒ STD ☐ OPTION	☒ STD ☐ OPTION	
1 HOLE(S) _____ mm	PISTONS	2 HOLE(S) _____ mm

FRONT	ANTI-ROLL BAR	REAR
2.3	mm	2.9 mm

FRONT	RIDE HEIGHT	REAR
7	mm	8.5 mm

FRONT	WIDTH	REAR
252	mm	262 mm

BRAND	TIRES	CONTROLLED
HotRace		☐ YES ☒ NO
LEFT FRONT RIGHT	DIAMETER	LEFT REAR RIGHT
66 mm 66 mm	73 mm 73 mm	

FRONT	WHEEL PLATE	REAR
☐ YES ☒ NO		☐ YES ☒ NO

BODY
Hyper

BUMPER WEIGHT & BODY POSITION
WEIGHT 0 g 0 g 0 g
BODY POSITION _____ mm

FRONT CARBON PLATE (R0274)
☐ YES ☒ NO

REAR BODY MOUNT
☒ PLASTIC (R0373)
POSITION 1 2
SIDE HEIGHT 20 mm

CARBON (R0337)
POSITION (R0337) 1 2 3
SPACER _____ mm
POSITION LOW HIGH
LIGHT WEIGHT (R0349)
POSITION 1 2

SHOCK TOWER
R0081 R0336
R0081W R0336W

LOWER ARM PLATE
☐ R0355W ☒ R0355N ☐ R0353
☒ YES ☐ NO

KNUCKLE BASE
SPACER 1 mm
☒ STANDARD (15.5) ☐ R0314B (13.5)

CASTER	SPACER
2 mm	0 mm
SWING SHAFT ☐ 64 ☒ 62 ☐ 60 ☐ 60 (90deg.)	

CHASSIS STIFFENER
☒ NO ☐ SCREW ☐ CARBON (R0393)
TOE ANGLE 2.5 deg.
HOLDER ☒ 20 ☐ 22
SUS BUSH 2 1
SWING SHAFT ☐ 54 ☒ 54R (90deg.) ☐ 56
MATERIAL ☐ STANDARD ☒ HARD

CENTERING PLATE
☒ STD ☐ REV
15 mm

WEIGHT / CARBON STIFFENER
WEIGHT ☐ MIDDLE ☐ RIGHT ☐ LEFT
ADDITIONAL WEIGHT _____ g
TOTAL CAR WEIGHT 2370 g
☐ CARBON (2P) ☐ CARBON (5P) ☒ BRASS (R0280)
CARBON STIFFENER ☐ MIDDLE CARBON

UPPER SUS BUSH	☐ SOFT ☐ HARD
UPPER SUS HOLDER	☐ STANDARD ☐ HARD ☒ ALUMINUM
SIDE SCREW	☐ YES ☒ NO
UPRIGHT UPPER	☐ STANDARD ☐ -1 ☒ 0 ☐ +1
CENTERING (R0328) / OFFSET BUSHING (R0327)	☒ YES ☐ NO
UPRIGHT LOWER	☐ STANDARD ☒ HARD
SUS ARM UPPER	☐ STANDARD ☒ HARD
SUS ARM LOWER	☐ STANDARD ☒ HARD
LOWER ARM END	☐ SOFT ☒ HARD ☐ OLD ☒ NEW
LOWER SUS HOLDER	☐ STANDARD ☒ HARD ☐ ALUMINUM
LOWER SUS BUSH	☐ SOFT ☒ HARD ☒ IN ☐ OUT
ONE WAY	☒ STANDARD ☐ 8mm (R0333)
STOPPER	☐ YES ☐ NO

SPACER	CAMBER
0 mm	2 deg.
AXLE SPACER .7 mm	
☐ YES ☐ NO	
DOWN STOP +1 mm	

SHOCK POS	SUS BUSH	SPACER	CAMBER
	1-2-3-4-5-6	2 mm	3 deg.
		AXLE SPACER .5 mm	
		☐ YES ☐ NO	
		DOWN STOP 8 mm	
		MATERIAL ☐ STANDARD ☒ HARD	
		LOWER ARM PLATE ☐ 0 ☐ 1.5 ☒ 3.0	

SERVO SAVER
STEERING PLATE ☐ 9mm ☒ 10mm ☐ 11mm (STD)
POSITION ☐ FORWARD ☒ MIDDLE ☐ BACKWARD
TIGHTENING a lot mm
SERVO SAVER TYPE ☐ PLASTIC ☒ ALUMINUM (R0259)
SERVO SAVER POSITION ☒ FORWARD ☐ MIDDLE
SPACER 2 mm
SPRING ☐ SOFT ☒ HARD

UPPER PLATE TYPE CUT
☒ STD
STIFFENER (R0388)
WEIGHT ☐ 15g (T096B) ☐ 10g (SMJ3517 x2) ☐ 7.5g (SMJ3518) ☐ 5g (SMJ3517)
R0390 R0391 R0389 R0363 R0392