

DATE	TRACK		TRACTION	HIGH	LOW
DRIVER	☐ ASPHALT ☐ CARPET ☐ FLAT ☐ BUMPY		TEMP.	AIR	TRACK
EVENT	BEST LAP TIME	QUALIFYING POSITION	FINAL POSITION		

REAR DAMPER SPRING

☐ SOFT ☐ MEDIUM ☐ HARD ☐ OTHERS

LENGTH /mm

DOWN STOP /mm

FRONT **REAR**

RIDE HEIGHT SPACER mm

RIDE HEIGHT /mm

PIVOT BALL SPACER FR RR /mm

RIDE HEIGHT /mm

RIDE HEIGHT /mm

FRONT SPRING

☐ SOFT ☐ MEDIUM ☐ HARD ☐ OTHERS

CAMBER °

CASTER SPACERS /mm

SPACERS /mm

SHIMS シム /mm

WIDTH SPACERS /mm

FRONT BRACE ☐ YES ☐ NO

KINGPIN OIL /CST

TOE ANGLE

ACKERMANN /mm

BATTERY POSITION

WIDTH 全幅 /mm

WIDTH 全幅 /mm

SIDE SPRING

☐ SOFT ☐ MEDIUM ☐ HARD ☐ OTHERS

SIDE TUBE OIL /CST

LENGTH /mm

RIDE HEIGHT

AXLE POSITION

DIFFERENTIAL SETTING

☐ SPOOL ☐ BALL DIFF

☐ TIGHT ☐ MEDIUM ☐ LOOSE

TIRE SETTING

FRONT	REAR
TIRE	TIRE
DIAMETER /mm	DIAMETER /mm
ADDITIVE	ADDITIVE
ADDITIVE TIME /MINS	ADDITIVE TIME /MINS
ADDITIVE AREA	ADDITIVE AREA

MOTOR

PINON GEAR T SPUR GEAR T

ROTOR /mm

MOTOR TIMING °

FINAL RATIO

ROLLOUT

ESC

BATTERY

SETUP

BODY

TOTAL WEIGHT /grs

MEMO