

DATE	2025 / 10 / 19	TRACK	KARP	TRACTION	HIGH ☐ ☐ ☒ ☐ ☐ LOW
DRIVER NAME	SHOTA WATANABE	CONDITION	☒ CARPET ☐ ASPHALT	TEMP.	AIR 28 TRACK
EVENT	EPS-J KARP	BEST LAP TIME	8.4s	QUALIFYING POSITION	1
				FINAL POSITION	1

LENGTH 12.2 /mm

REAR DAMPER SPRING
☐ SOFT
☒ MEDIUM
☐ HARD
 OTHERS _____

DOWN STOP 3.0 /mm

FRONT

UPRIGHT SPACER 1.0 mm

RIDE HEIGHT 3.4 /mm

PIVOT BALL SPACER 2 /mm

RIDE HEIGHT 3.5 /mm

REAR

RIDE HEIGHT 3.5 /mm

FRONT SPRING
☐ SOFT ☐ MEDIUM
☒ HARD OTHERS _____

CASTER
☐ 3°
☒ 4°
☐ 5°

CAMBER 1.5 °

SHIMS シム
 1.5 /mm
 1.5 /mm

WIDTH SPACERS 0.3 /mm

FRONT BRACE
☒ YES ☐ NO

KINGPIN OIL
 タミヤフリクション /CST
 Medium

TOE ANGLE 1 °

ACKERMANN 0 /mm

POD LINK POSITION ☒

WIDTH 全幅 166 /mm

WHEELBASE
☒ LONG
☐ SHORT

CHASSIS BRACE
☒ SIDE BRACE
☐ T BRACE

WIDTH 全幅 172 /mm

SIDE SPRING
☐ SOFT ☒ MEDIUM
☐ HARD
 OTHERS _____

SIDETUBE OIL KYOSHO 15000 /CST

LENGTH 1.2 /mm

RIDE HEIGHT
☐ 0.00
☐ -0.25
☒ -0.50
☐ -0.75
☐ -1.00
☐ -1.25
☐ -1.50
☐ -1.75
☐ -2.00

AXLE POSITION
☐ UP ☒ DOWN

DIFF SETTING
☒ SPOOL
☐ BALL DIFF
☐ TIGHT
☐ MEDIUM
☐ LOOSE

TIRE SETTING

FRONT	REAR
TIRE AXX35	TIRE AXX30
DIAMETER 40.5 /mm	DIAMETER 41.5 /mm
ADDITIVE SXT3.0	ADDITIVE SXT3.0
ADDITIVE TIME 30 /MINS	ADDITIVE TIME 90 /MINS
ADDITIVE AREA	ADDITIVE AREA

MOTOR Team Powers Act.V5 3.5T TURNS

PINON GEAR 25 T SPUR GEAR 90 T

ROTOR 12.3 /mm MOTOR TIMING 24 °

FINAL RATIO ROLLOUT

ESC HOBBYWING SETUP

BATTERY SMC 8000 BODY perfect10UL TOTAL WEIGHT 734 /grams

MEMO

- DTY-D40006 Servo Saver Horn for Xray Saver (7.0)
- ROCHE-220350 P12V2 フロントブレース Flex
- ky378 3Dバンパーロング
- フリクションスプリング上下1巻カット
- サーボ横5g