

DATE	17 / 12 / 2022	TRACK	EECC	TRACTION	HIGH ☐ ☐ ☒ ☐ ☐ LOW
DRIVER NAME	SPASHETT	CONDITION	☒ CARPET ☐ ASPHALT	TEMP.	AIR ☐ TRACK ☐
EVENT	EECC	BEST LAP TIME		QUALIFYING POSITION	1
				FINAL POSITION	1

LENGTH 13.7 /mm

DOWN STOP 7.5 /mm

REAR DAMPER SPRING

☐ SOFT ☐ MEDIUM ☐ HARD

OTHERS roche pink

FRONT

RIDE HEIGHT 3.4 /mm

PIVOT BALL SPACER 0 FR 0 RR/mm

RIDE HEIGHT 3.5 /mm

REAR

RIDE HEIGHT 3.6 /mm

FRONT SPRING

☐ SOFT ☐ MEDIUM ☐ HARD

OTHERS 475

CAMBER 1.0

CASTER 4.25

KINGPIN OIL red lube /CST

HEIGHT SPACERS 0.25 /mm

SPACERS 2.0 /mm

SPACERS 2 /mm

WIDTH SPACERS 0.4 /mm

TOE ANGLE 0

ACKERMANN 0 /mm

BATTERY POSITION

WIDTH 全幅 kit /mm

WIDTH 全幅 172 /mm

SIDE SPRING

☐ SOFT ☐ MEDIUM ☐ HARD

OTHERS sch silver

SIDE TUBE OIL 5000 /CST

LENGTH 1.0 /mm

RIDE HEIGHT

0.00 ☐ -0.25 ☐ -0.50 ☐ -0.75 ☒ -1.00 ☐ -1.25 ☐ -1.50 ☐ -1.75 ☐ -2.00

AXLE POSITION ☐ UP ☒ DOWN

DIFF SETTING

☒ SPOOL ☐ BALL DIFF

☐ TIGHT ☐ MEDIUM ☐ LOOSE

TIRE SETTING

FRONT

TIRE HAG

DIAMETER 40.5 /mm

ADDITIVE SPIDER BLUE

ADDITIVE TIME 10 /MINS

ADDITIVE AREA

REAR

TIRE HAG

DIAMETER 41 /mm

ADDITIVE SPIDER BLUE

ADDITIVE TIME 30 /MINS

ADDITIVE AREA

MOTOR 13.5 TURNS

PINON GEAR 41 T

SPUR GEAR 80 T

ROTOR tep1119 /mm

MOTOR TIMING 44

FINAL RATIO 66.02

ROLLOUT 66.02

ESC HW

BATTERY IP8800

SETUP BLINKY

BODY SUPERRAD

TOTAL WEIGHT 735 /grams

MEMO

NOS Reactive Proto, Low height steering block OPT-0133 2mm under and 1.4 on top.

No front spring sag but no compression.