

DATE		CONDITION	☐ FLAT ☐ BUMPY ☐ TIGHT ☐ OPEN	TRACTION	HIGH LOW
DRIVER		☐ CARPET	☐ ASPHALT ☐ INDOOR ☐ OUTDOOR	TEMP °C	AIR TRACK
EVENT		BEST LAP TIME		QUALIFYING POSITION	
				FINAL POSITION	

FRONT

SHOCK SPACER /mm

UPPER ARM SPACER /mm (FF) /mm (FR)

SPACER /mm

STEERING PLATE ☐ 0 ☐ +3

BODY UPSTOP /mm

ROLL-CENTER SPACER /mm (FF) /mm (FR)

SHOCK SPACER /mm

TRACK WIDTH 0mm +1mm

DROOP /mm

ACKERMANN SPACER /mm

CENTER PLATE ☐ (8.0) ☐ (8.5)

STEERING SPACER /mm

FRONT DIFF ☐ DIFF # /CST

WHEEL HUB ☐ 4.0mm ☐ 5.0mm

WHEEL SPACER /mm

DIFF POSITION ☐ UP ☐ DOWN

SHOCK ABSORBER
OIL /CST
LENGTH /mm
REBOUND %
SPRING ☐ 2.5 ☐ 2.6 ☐ 2.7 ☐ OTHERS
ABSORBER MEMBRANCE
PISTON ☐ 3 HOLES ☐ 4 HOLES

SHOCK ABSORBER
RIDE HEIGHT /mm
CAMBER °
CASTER ☐ 4° ☐ 5°
SWAY BAR ☐ 1.3 ☐ 1.4 ☐ OTHERS
TOE ANGLE °

REAR

SHOCK SPACER /mm

UPPER ARM SPACER /mm (RF) /mm (RR)

SPACER /mm

STEERING PLATE ☐ 0 ☐ +3

ROLL-CENTER SPACER /mm (FF) /mm (FR)

SHOCK SPACER /mm

TRACK WIDTH 0mm +1mm

DROOP /mm

REAR LINK POSITION

WHEEL HUB ☐ 4.0mm ☐ 5.0mm

WHEEL SPACER /mm

ANTI-ROLL BAR POSITION ☐ INNER ☐ OUTER

SHOCK ABSORBER
OIL /CST
LENGTH /mm
REBOUND %
SPRING スプリング ☐ 2.5 ☐ 2.6 ☐ 2.7 ☐ OTHERS
ABSORBER MEMBRANCE
PISTON ☐ 3 HOLES ☐ 4 HOLES

SHOCK ABSORBER
RIDE HEIGHT /mm
CAMBER °
CASTER ☐ 5° ☐ 4°
SWAY BAR ☐ 1.2 ☐ 1.3 ☐ OTHERS
TOE ANGLE °

FRONT BRACE D30012

WEIGHT BALANCE g

MAIN CHASSIS ☐ GRAPHITE ☐ ALUM (FLEX)

CHASSIS T-BRACE ☐ ALUM ☐ BRASS (10g)

FRONT BUMPER WEIGHT D30014

FRONT BRACE O10286

FRONT DIFF WEIGHT O30015

MULTI-FLEX CHASSIS

WEIGHT BALANCE g

WEIGHT BALANCE g

WEIGHT BALANCE g

CUT CUT

MULTI-FLEX CHASSIS

TRACK WIDTH
FRONT /mm
REAR /mm

SERVO HORN
SPACER /mm
/mm
☐ KIT ☐ ALUM

UPPER DECK
☐ KIT (SINGLE PIECE)
☐ 1.6mm ☐ 2.0mm

TIRE SETTING
FRONT & REAR
TIRE
INSERT
WHEEL
ADDITIVE
ADDITIVE TIME
Fr - /MINS Rr - /MINS

MOTOR /mm
PINON GEAR T SPUR GEAR T
ROTOR /mm
FINAL RATIO
MOTOR TIMING °
ESC SETUP
BATTERY ☐ SHORTY BODY TOTAL WEIGHT /g

NOTES