

Driver: _____ Motor: _____
 Date: _____ Endbell Timing: _____
 Track: _____ Rotor: _____
 Surface: _____ Final Ratio: _____
 Temperature: _____

Max. ESC Temperature: _____ Min. Battery Voltage: _____
 Max. Motor Temperature: _____ Max. Motor RPM: _____



Type	Item	Value							
General Setting	Running Mode	Fwd/Brk		Fwd/Rev/B		Fwd/Rev			
	Reverse Force	25%		50%		75%		100%	
	Cutoff Voltage	Disabled		Auto		_____(3.0-11.1 Adjustable)			
	ESC Thermal Protection	105℃/221		125℃/257		Disabled			
	Motor Thermal Protection	105℃/221		125℃/257		Disabled			
	BEC Voltage	6.0V		7.4V					
	Remote Off	Enabled		Disabled					
	Sensor Mode	Full Sensored		Sensored/Sensorless Hybrid					
Throttle Control	Throttle Rate Control	_____(1-30 Adjustable)							
	Throttle Curve	Linear		Customize					
	Neutral Range	4%		6%		8%			
	Coast	_____(0%-20% Adjustable)							
	Drive Frequency	1K	2K	4K	8K	12K	16K		
Brake Control	Drag Brake	_____(0%-100% Adjustable)							
	Brake Force	0%	12.5%	25%	37.5%	50%	62.5	75%	87.5% 100%
	Initial Brake Force	=Dragbrake		_____(0%-50% Adjustable)					
	Brake Rate Control	_____(1-20 Adjustable)							
	Brake Curve	Linear		Customize					
	Brake Frequency	0.5K		1K		2K		4K	
	Brake Control	Linear		Traditional		Hybrid			
Timing	Boost Timing	_____(0-60 Adjustable)							
	Timing Activation	RPM		Auto					
	Boost Start RPM	_____(500-35000RPM Adjustable)							
	Boost End RPM	_____(3000-60000RPM Adjustable)							
	Turbo Timing	_____(0-64 Adjustable)							
	Turbo Delay	Instant _____ (0.05-1.0S Adjustable)							
	Turbo Increase Rate (deg/0.1sec)	6	12	18	24	30	Instant		
	Turbo Decrease Rate (deg/0.1sec)	6	12	18	24	30	Instant		