

M300FX-III

1/18 SCALE ELECTRIC 2WD COMPETITION CAR

SETTING SHEET

SETTING SHEET

DATE _____

● Name: _____

Environment: ☐ Indoor ☐ Outdoor

Grip Level: Low Medium High

Temp: °C Humidity: % Track Temp: °C

● Reactive Caster Angle ☐☆-10° ☐-5°

●Front Ride Height Shim ☐2.0mm× ☐1.5mm×
☐1.0mm× (mm

● Pivot Ball Position

Upper Arm	Lower Arm

● Front Spring ☐SS ☐S ☐MS ☐☆M ☐H
φ0.4(黒) φ0.45(金) φ0.5(黒) φ0.5(銀) φ0.55(黒)

● Toe Angle: ◦ ● Camber Angle: ◦

● Side Spring

☐ ☆S (銀) ☐ M (黒) ☐ H (銀)

☐ Other ()




ロアブレースにタッチしてから

スプリングテンション

● Bearing Holder

Spacer Position



56

54

52

50

48

☐ Other or Optional Holder:

● Roll Out:

Pinion Gear:	T
Spur Gear:	T

● Motor: _____ Turns
 Rotor: _____ mm Timing: _____ °

● Battery: / mAh

● Result:

Qualification Position:
Final Position:

memo

● Front Damper Oil

#

● Kingpin Shims

mm

● Ride Height

mm

● Caster Shims

0 0.5 1.0 1.5

☐ ☐ ☐ ☆ ☐

1.5 1.0 0.5 0

● Front Brace

☐ Yes ☐ No

● Lower Susp. Mount

☐ ☆-0.5 ☐ 0 ☐ +0.5

● Size:

mm

● Tire Additive

● Additive Time

Min.

● Application:

☐ ☐ ☐ ☐

● Servo Horn Position

1

2 ☆

3

● Shock Position

1

2

3 ☆

4

● Front Tire

● Front Wheel

● Length (A)

mm

● Preload (B)

mm

● シャフトスペーサー

mm

● Damper Oil

#

● Spring

☐ ☆S (銀) ☐ M (黒) ☐ H (銀)

☐ Other ()

☐ Damper Tubes

☐ Side Shock

● Damper Oil

#

● Ride Height

mm

● Rear Droop:

mm

● Ride Height

mm

● Rear Tire

● Rear Wheel

● Size:

mm

● Tire Additive

● Additive Time

Min.

Application:

☐ ☐ ☐ ☐

1

mm

mm

1

1

1

mm

☆ Indicates standard item or setting