1/10TH SCALE WORLD GT CAR

M500WGT-X

SETTING SHEET

DATE

● Name

● Track / Event

Environment ☐Indoor ☐ Outdoor

Surface ☐Asphalt ☐Carpet ☐ Bumpy ☐ Smooth

Traction Low Medium High

Air temp. ℃ Track temps. ℃ Humidity %

●Body

●Reactive Caster Angle ☐☆−10° ☐−5°

● Front Ride Height Shim

●Front Axle Fwd ☐−0.5 ☐ 0 Trailing ☐☆+0.5

●Pivot Ball Position Upper Arm Lower arm

●Front Spring ☐SS φ0.4 ☐S φ0.45 ☐MS φ0.5 ☐☆M φ0.5 ☐H φ0.55

● Toe ☐Out ☐In °

● Camber °

● Side Spring ☐☆Inside ☐ Outside

☐☆S ☐M ☐H

☐ Other ( )

☐Side Spring Tension °

# of turns after contact with lower brace

●Bearing Holder Spacer Position +2 +1 ±0 −1 −2

56 54 52 50 48

☐ ☐☆ ☐ ☐ ☐ ☐☆ ☐ その他☐

●Ratio Pitch DP Pinion T Spur T

● Motor / Turns

Rotor mm Timing °

● Battery / mAh

● Position

☐Forward ☐ Backward ☐ Sideway

※1セル及びショートサイズのみ

● Result Qualification Final

# of Lap Lap time

Notes

●Front Damper Oil

#

●Ride Height

mm

●Kingpin Shims

×

×

×

×

●Front Droop mm

● Caster shim

0 0.5 1.0 1.5

☐ ☐ ☐☆ ☐

1.5 1.0 0.5 0

● Front Brace

☐Yes ☐No

●Bumpsteer Spacer

mm

● Additive

● Time

● Surface

● Notes

mm

● Ackermann

☐☆ 1

☐ 2

☐ 3

● Spacer

mm

●Front Tire

●Front Wheel

●Horn

☐☆B-29S

☐ Other

● Length (A)

mm

● Preload (B)

mm

● Piston ☐φ1x1.1mm ☐φ2x1.1mm ☐φ3x1.1mm ☐φ1x1.1mm ☐☆φ2x1.1mm ☐φ3x1.1mm

● Oil

#

● Spring

A

B

☐☆Damper Tubes

☐ Side Shock

●Oil

#

●Ride Height

mm

●Rear Droop

mm

● Additive

● Time

● Surface

●Notes

mm

●Ride Height

mm

●Rear Tire

●Track Width mm

●Rear Wheel

☆は、キット標準

Arn0