Your Fri	nd in RC Need			Driver: City:	e: 1/25/2010 r: Mikihisa Yanai Corner r: Gunma,Japan t: CRC CUP			nief2009	
Front end MH200	9								
Spring:	BMI .020"	Caster:	5°	Camber:	1,0°	Reactive caster: 3,5mm		3,5mm	
Ride height:	2,0mm	Bumpsteer:	Yes	Toe in/out:	out 0,5mm	Droop: -		-	
Front ball studs:	Short	Placement:	Outer holes	Studshim F:	-	Kingpin grease: -		-	
Rear ball studs:	Medium	Placement:	Outer holes	Studshim R:	-	Bumpsteer spacers: 1,0mm			
Servo mount type:	Flat	Servo saver:	Small	Ball studs:	Short	servo position: 12mm Front			
Comments:				4					
Front tires									
Brand & Comp.:	YOKOMO Firm	n	Diameter:	39,5mm	Rims:	TRC	Car width:	std	
Tire treatment									
Time:	5min	Pr	oduct brand:	Ground Effect	s				
Surface:	Inside					Outside			
Comments:									
Rear end									
Shock body:	SILVA		Shock oil:	#350			Shock spring:	Copper 16.0	
Dampner grease:			Side spring:	AE Silver		Springs on dampners: -			
Rear Ride height:		Center	Ride height:			Ride height adjuster: #2,5			
Rear droop:			·····g····	_,-,	Shock position (top/end): crc/2mm				
Comments:	0,0					onoon poortio	(top, oa, .	0.0, =	
Comments.									
Rear tires									
Brand & Comp.:	YOKOMO Medium Hard Diameter:			40,5mm	Rims:	TRC	Car width:	171mm	
Tire treatment									
Time:				Ground Effect	S				
Surface:	Inside					Outside			
Comments:									
Electronics:			1						
			ESC FW Ver:		ESC setup:	IVO PROOFILOS			
	SANWA RX-451		RollOut:		-	KO PDS951ICS			
			Timing:		-	LRP 12.5mm			
Battery Position: Back Gearing:			94/24	Battery:	SMC C-MAX 5	5300mA			
Track Condition				Misc:					
Surface:	Smooth		Chassis:	2.5mm					
Traction:	High			Weight:					
Composition:	Carpet			Body:	PARMA SPEE	D8HD			
Race				Comments:					
Qualifying:	5								
Finish:	3								