

FLOW X STOCK SPEC - V5.1 / V5.2

Driver:					Motor:	Rotor:		mm			
Date:					Timing:	°		Gearing:			
Event:					Battery:	Charged to:		V			
Track:					Fan:	ESC		Motor			
Racing Class:					Qualify:	Finish:		ESC Temp.:	blinks	Motor Temp.:	blinks
Size:	Small	Medium	Large	Extra Large	Air Temp.:		Track Temp.:				
Surface:	Dirt	Carpet	Astroturf	Asphalt	Car:						
Traction:	Low	Medium	High	Very High	Radio:						
Moisture:	Dry	Damp	Wet	EPA:					% Throttle	% Brake	
Condition:	Indoor	Outdoor	Dusty	Hard Packed	EXPO:					% Throttle	% Brake
	Bumpy	Grooved	Smooth	Loamy							

MODE		LED	0	1	2	3	4	5	6	7	8	9	10	
1	Brake	Auto Brake (%)												
		Brake Type	F		SEMI X	X-Stock	BD3	BDX-S	-					
		Initial Brake (%)	S											
4	Throttle	Initial Drive (%)												
		IDFC		F										
		Torque Feel												
		Timing (°)												
		Ramp (°/10kRpm)												
		Delay (kRpm)		F	F									
		Protection												
10														

no value / hidden mode
Factory default settings
F LED blinking fast
S LED blinking slow

Value Summary:

NOTES