

FLOW X STOCK SPEC - V5.1 / V5.2

Driver:					Motor:	Rotor:	mm	
Date:					Timing:	°	Gearing:	
Event:					Battery:	Charged to:	V	
Track:					Fan:	ESC	Motor	
Racing Class:	Qualify:	Finish:			ESC Temp.:	blinks	Motor Temp.:	blinks
Size:	Small	Medium	Large	Extra Large	Air Temp.:	Track Temp.:		
Surface:	Dirt	Carpet	Astroturf	Asphalt	Car:			
Traction:	Low	Medium	High	Very High	Radio:			
Moisture:	Dry	Damp	Wet			EPA:	% Throttle	% Brake
Condition:	Indoor	Outdoor	Dusty	Hard Packed	EXPO:	% Throttle	% Brake	
	Bumpy	Grooved	Smooth	Loamy				

MODE		LED	0	1	2	3	4	5	6	7	8	9	10	
1	Brake	Auto Brake (%)												
		Brake Type	F		SEMI X	X-Stock	BD3	BDX-S	-					
		Initial Brake (%)	S											
4	Throttle	Initial Drive (%)												
		IDFC		F										
		Torque Feel												
		Timing (°)												
		Ramp (°/10kRpm)												
		Delay (kRpm)		F	F									
		Protection												
10														

 no value / hidden mode
 Factory default settings
 F LED blinking fast
 S LED blinking slow

Value Summary:

NOTES