

NOSRAM

POWER - SETUP - SHEET

HD STOCK SPEC - V5.1 / V5.2

Driver:					Motor:		Rotor:		mm						
Date:					Timing:		°		Gearing:						
Event:					Battery:		Charged to:		V						
Track:					Fan:		ESC		Motor						
Racing Class:			Qualify:		Finish:		ESC Temp.:		blinks		Motor Temp.:		blinks		
Size:		Small		Medium		Large		Extra Large		Air Temp.:		Track Temp.:			
Surface:		Dirt		Carpet		Astroturf		Asphalt		Car:					
Traction:		Low		Medium		High		Very High		Radio:					
Moisture:		Dry		Damp		Wet				EPA:		% Throttle		% Brake	
Condition:		Indoor		Outdoor		Dusty		Hard Packed		EXPO:		% Throttle		% Brake	
		Bumpy		Grooved		Smooth		Loamy							

MODE			LED		0	1	2	3	4	5	6	7	8	9	10
1	Brake	Auto Brake (%)			0	1	3	5	7	9	11	13	15	20	25
2		Brake Type	F		SEMI X	X-Stock	BD3	BDX-S	-						
3		Initial Brake (%)	S		0	1	3	5	7	9	11	13	15	20	25
4	Throttle	Initial Drive (%)			-	3	5	7	9	12	15	18	21	24	27
5		IDFC		F	0	1	2	3	4	5	-				
6		Torque Feel			0	1	2	3	4	5	-				
7		Timing (°)			0	15	20	25	30	35	40	45	50	55	60
8		Ramp (°/10kRpm)			-	10	12	14	16	18	20	25	30	35	40
9		Delay (kRpm)		F	F	3,5	5	7,5	10	12,5	15	-			
10 Protection					ALL	ESC	NONE	-							

no value / hidden mode

Factory default settings

FLED blinking fast

SLED blinking slow

Value Summary:

NOTES