

MTC2R SETUP SHEET

NAME:	DATE:
TRACK:	RACE:
TRACK SURFACE:	CARPET ☐ ASPHALT ☐
LAYOUT:	TECHNICAL ☐ MIXED ☐ FAST ☐
TRACTION:	LOW ☐ MEDIUM ☐ HIGH ☐
ELECTRONICS	
SERVO:	ESC:
BATTERY:	MOTOR/TIMING:
NOTES:	
TIRES	
BRAND/TYPE F/R:	
ADDITIVE F/R:	
ADDITIVE TIMING F/R:	
WARMER° F/R:	
TRANSMISSION	
PINION:	SPUR: A2248D(Alu): ☐
DIFF OIL CST:	OIL WEIGHT (qty.):
BELT TENSION:	FRONT: 1 2 3 4 5 6 7 REAR: 1 2 3 4 5 6 7
SHOCK 'S	FRONT: REAR:
SHOCK CASE:	
PISTON:	
OIL:	
SPRING:	
LENGTH:	
ANTI ROLL BAR	
FRONT:	REAR:
OPTIONAL WEIGHT	
A2423 ☐	A2424 ☐
A2425 ☐	A2704 ☐
A2705 ☐	
BODYSHELL	
TYPE:	WING TYPE:
WING POS:	OVERALL WEIGHT:
STIFFENER: ☐	(mm)

FRONT SUSPENSION

☐ A2148
☐ A2148-H
☐ ACTIVE
☐ FIXED

SHIM (mm) CASTER (°) SHIM (mm)

NO BODY STOP ☐ STEERING ANGLE OUTSIDE

SHIM UNDER A2435C (mm) INSIDE

SHIM (mm)

HEX (mm) CAMBER (°)

SHIM (mm) TOE (°)

RIDE HEIGHT (mm)

STEERING ROD POSITION

A2147F ☐
 A2467F (-1mm) ☐

FF (mm) FR (mm)

A2158 FRONT BRACE

INSIDE ☐
 OUTSIDE ☐

A2529 (ALU) ☐ SERVOHORN (mm) DOWNSTOP (mm)

REAR SUSPENSION

☐ A2148
☐ A2148-H
☐ ACTIVE
☐ FIXED

SHIM (mm) CASTER (°) SHIM (mm)

RR (mm) RF (mm)

ROD POSITION

SHIM (mm)

HEX (mm)

SHIM (mm)

CAMBER (°)

TOE-IN (°)

RIDE HEIGHT (mm)

DOWNSTOP (mm)

INSIDE ☐
 OUTSIDE ☐

A2530 (ALU) ☐

CHASSIS/FLEX/WEIGHT DISTRIBUTION

A2414: ☐
 A2415: ☐
 A2434: ☐

F/R DISTRIBUTION

Gr Gr

H2412 (18g) ☐

Gr Gr

1 2 3 4 MM SCREW

BATTERY POSITION

Fr Rr

A2419

OVERALL WEIGHT (Grs)

UPPERDECK SETTING

A2170: ☐

CUTTING FRONT:

MM FLEX SETTING:

A2166: ☐

CUTTING REAR:

OTHER UPPERDECK:

COMMENTS: