

TRACK CONDITION

ENVIRONMENT: INDOOR ☐ OUTDOOR ☐COMPOSITION: CARPET ☐ ASPHALT ☐TRACTION: LOW ☐ MEDIUM ☐ HIGH ☐LAYOUT: SLOW ☐ MIXED ☐ FAST ☐SURFACE: BUMPY ☐ SMOOTH ☐

NOTES

ELECTRONICS

MOTOR: _____ TIMING: _____

PINION: _____ SPUR: _____

ESC: _____

BATTERY: _____

SERVO: _____

RECEIVER: _____

SHOCK ABSORBERS

FRONT _____ REAR _____

PISTON: _____ PISTON: _____

OIL: _____ OIL: _____

SPRING: _____ SPRING: _____

REBOUND: _____ REBOUND: _____

NOTES

ANTI-ROLL BAR

FRONT: 1.0 ☐ 1.1 ☐ 1.2 ☐ _____ ☐REAR: 1.0 ☐ 1.1 ☐ 1.2 ☐ _____ ☐

TIRES & WHEELS

TIRE: _____

INSERT: _____

WHEEL: _____

TREATMENT: _____

NOTES

REAR DIFFERENTIAL

OIL: _____ / _____ g

AERODYNAMICS

BODY: _____

WING: _____

WING POSITION: _____ mm


BODY POSITION

HORIZONTAL: _____ mm


VERTICAL

FRONT BODY
HEIGHT & POSITION

_____ mm

REAR BODY POSITION
A2407C

_____ mm

REAR BODY POSITION
A2416B

_____ mm



NOTES

STEERING LIMITER

☐ A2304 (5.0mm)☐ A2305 (5.5mm)☐ A2306 (6.0mm)

STEERING ANGLE

IN: _____

OUT: _____

SHOCK POSITION

UPPER ARM POSITION
FR (mm)

FF (mm)

LOWER ARM POSITION
FR (mm)


FF (mm)

FRONT

A2529 POSITION



A2530 POSITION

UPPER ARM POSITION
RF (mm)

RR (mm)

LOWER ARM POSITION
RF (mm)

RR (mm)

REAR


A2421 USED - SHIM (mm)

☐ YES☐ NO

STEERING ROD POSITION

☐ REAR☐ FRONT

UPPER ARM POSITION (CASTER)

REAR/5° ☐☐ FRONT/4°

SHIM UPRIGHT TOP (mm)

CAMBER (°)

TOE (°)

OFFSET (mm)

SHIM STEERING ROD (mm)

SHIM UPRIGHT BOTTOM (mm)

RIDE HEIGHT (mm)

DOWNSTOP (mm)


ACKERMANN SHIM (mm)

HORN SHIM (mm)

HORN LENGTH (mm)

TYPE SERVO HORN

UPPER ARM POSITION (CASTER)

FRONT/4° ☐☐ REAR/3°

SHIM UPRIGHT TOP (mm)

CAMBER (°)

TOE (°)

OFFSET (mm)

☐ A2219☐ A2224

RIDE HEIGHT (mm)

DOWNSTOP (mm)

SHOCK POSITION

REAR TIE ROD POSITION

☐ FRONT☐ REAR

SHIM TIE ROD (mm)

SHIM UPRIGHT BOTTOM (mm)

A2422 (10g)

A2422 (10g)

A2422 (18g)

A2422 (10g)

A2422 (10g)

BATTERY ROD POSITION FRONT ☐ REAR ☐

CHASSIS TYPE

MOTORMOUNT SCREW

FRONT/REAR WEIGHT
DISTRIBUTION HOLE

WEIGHT (g): _____

OPTIONAL WEIGHT

A2424 - 52g


A2425 - 20g

A2705 - 15g

A2706 - 10g

BELT TENSION
FRONT POSITION

REAR POSITION

1PC. UPPER DECK TYPE ☐ 2PC. UPPER DECK TYPE ☐

UPPER DECK SCREW

COMMENTS