





DRIVER	Ronald				
DATE	30-03-2021				
TRACK	Carpet ☐ Asphalt ☒	Arena 33			
TRACTION	☒ LOW	☐ MEDIUM	☐ HIGH		
LAYOUT	☐ SLOW	☒ MIXED	☐ FAST		
TEMP °C	AIR	15	TRACK		
ELECTRONICS					
ESC	LRP	ESC SET	MOTOR LRP 5.0t		
SERVO	Highest	RECEIVER	493	BATTERY LRP	
TIRES					
BRAND	Matrix ETS				
TYPE	36				
ADDITIVE	MR33 V3				
WARMER °C	FRONT	70	REAR	70	
TIME(min)	FRONT	10	REAR	10	
SHOCK ABSORBERS					
PISTON	FRONT	std	REAR	std	
SHOCK CASE	std		std		
OIL	Axon 30		Axon 35		
SPRING	7.0P		6.25		
LENGTH		9.5		9.5	
ANTI ROLL BAR DIAMETER FRONT/REAR					
FRONT	1.1	REAR	1.1		
REAR DIFFERENTIAL					
DIFF OIL CST (1,6g oil qty.)			6000 (1.5g)		
GEAR RATIO			(T)Spur/(T)Pinion*1,9=Ratio		
PINION	28	SPUR	108		
AERODYNAMIC SETTINGS					
BODY TYPE	Twister 0.7				
WING TYPE	Twister 0.7				
WING POS			(mm) +5		
BODY POSITION (see picture below)			(mm)  horizontal 4-5		
FRONT BODY HEIGHT & POSITION	REAR BODY POST A2407C	☒	REAR BODY POST A2416B	☐	
					
(mm) vertical 	48	(mm)	45	(mm)	
					

STEERING LIMITER

A2304 (5mm) ☐ A2305 (5.5mm) ☐ A2306 (6mm) ☒

STEERING ANGLE IN°

STEERING ANGLE OUT°

SHOCK POS (mm)

UPPER ARM POS. FR(mm)

FF(mm)

LOWER ARM POS. FR(mm)

FF(mm)

STEERING ROD POS (mm)

SHIM UPRIGHT L (mm)

SHIM UPRIGHT T(mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

UPPERARM POS. (CASTER)

REAR/5° ☐ FRONT/4° ☒

CAMBER/°

TOE OUT/°

OFFSET (mm)

FRONT

ACKERMANN SHIM (mm)

SHIM S HORN (mm)

LENGTH S HORN (mm)

TYPE SERVO HORN

A2529 POSITION

☐ INSIDE ☒ OUTSIDE

A2530 POSITION

☒ INSIDE ☐ OUTSIDE

UPPER ARM POS. RF(mm)

RR(mm)

LOWER ARM POS. RF(mm)

RR(mm)

SHOCK POS (mm)

TOE ROD POS (mm)

SHIM UPRIGHT L (mm)

SHIM UPRIGHT T (mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

UPPERARM POS. (CASTER)

FRONT/-4° ☒ REAR/-3° ☐

CAMBER/°

TOE IN/°

OFFSET (mm)

REAR

BATTERY POSITION FRONT ☐ **REAR** ☒

CHASSIS TYPE

MM SCREW

H2412 (18g) ☒ ☒ ☐ ☒ ☒

FRONT/REAR WEIGHT DISTRIBUTION HOLE# ☒ ☐ ☐ ☐ ☐ ☐

WEIGHT(g)

WEIGHT(g)

OPTIONAL WEIGHT

A2424 ☐ A2425 ☒ A2705 ☒ A2706 ☒

BELT TENSION

FRONT POS.

REAR POS.

A2419 SCREW

1pc. UPPERDECK TYPE ☒ **2.0**

2pc. UPPERDECK TYPE ☐

UPPERDECK SCREW

A2158 ☒ A2158 ☒

REMARKS

- 2mm shims below A2420 body mount plate
- A2425 battery weight for rear only
- 35g plate under battery (battery weighs 220g)