

DRIVER			
DATE			
TRACK	Carpet ☐ Asphalt ☐		
TRACTION	☐ LOW ☐ MEDIUM ☐ HIGH		
LAYOUT	☐ SLOW ☐ MIXED ☐ FAST		
TEMP °C	AIR	TRACK	
ELECTRONICS			
ESC	ESC SET	MOTOR	
SERVO	RECEIVER	BATTERY	
TIRES			
BRAND			
TYPE			
ADDITIVE			
WARMER °C	FRONT	REAR	
TIME(min)	FRONT	REAR	
SHOCK ABSORBERS			
PISTON	FRONT	REAR	
SHOCK CASE			
OIL			
SPRING			
LENGTH			
ANTI ROLL BAR DIAMETER FRONT/REAR			
FRONT		REAR	
REAR DIFFERENTIAL			
DIFF OIL CST (1,6g oil qty.)			
GEAR RATIO (T)Spur/(T)Pinion*1,9=Ratio			
PINION		SPUR	
AERODYNAMIC SETTINGS			
BODY TYPE			
WING TYPE			
WING POS		(mm)	
BODY POSITION (see picture below)		(mm)	
FRONT BODY HEIGHT & POSITION	REAR BODY POST A2407C	☐	REAR BODY POST A2416B
(mm) vertical	(mm)		(mm)

STEERING LIMITER ☐ A2304 (5mm) ☐ A2305 (5.5mm) ☐ A2306 (6mm)	STEERING ANGLE IN° STEERING ANGLE OUT° 	A2421 USED YES ☐ NO ☐ A2421 SHIM(mm) 	UPPERARM POS. (CASTER) REAR/5° ☐ ☐ FRONT/4° ☐
UPPER ARM POS. FR(mm) FF(mm) LOWER ARM POS. FR(mm) FF(mm) 	SHOCK POS (mm) STEERING ROD POS (mm) SHIM UPRIGHT L (mm) 	SHIM UPRIGHT T(mm) CAMBER/° TOE OUT/° OFFSET (mm) 	RIDE HEIGHT(mm) DOWNSTOP(mm)
FRONT			
A2529 POSITION ☐ INSIDE ☐ OUTSIDE A2530 POSITION ☐ INSIDE ☐ OUTSIDE	ACKERMANN SHIM (mm) SHIM S HORN (mm) LENGTH S HORN (mm) 	TYPE SERVO HORN 	UPPERARM POS. (CASTER) FRONT/-4° ☐ ☐ REAR/-3° ☐
UPPER ARM POS. RF(mm) RR(mm) LOWER ARM POS. RF(mm) RR(mm) 	SHOCK POS (mm) TOE ROD POS (mm) SHIM UPRIGHT L (mm) 	SHIM UPRIGHT T (mm) CAMBER/° TOE IN/° OFFSET (mm) 	RIDE HEIGHT(mm) DOWNSTOP(mm)
REAR			
WEIGHT(g) H2412 (18g) ☐ WEIGHT(g) 	WEIGHT(g) FRONT/REAR WEIGHT DISTRIBUTION HOLE# 	WEIGHT(g) WEIGHT(g) 	BATTERY POSITION FRONT ☐ ☐ REAR CHASSIS TYPE MM SCREW ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ A2419 SCREW ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ A2419 ☐
OPTIONAL WEIGHT A2424 ☐ A2425 ☐ A2705 ☐ A2706 ☐	BELT TENSION ☐ FRONT POS. ☐ REAR POS. ☐	2pc. UPPERDECK A2159 FRONT ☐ ☐ REAR ☐ ☐ 1pc. UPPERDECK TYPE A2151 (2mm) ☐ A2152 (1.6mm) ☐ 2pc. UPPERDECK A2162 ☐ ☐	SHOCK TOWER FRONT ☐ ☐ A2524F ☐ ☐ A2542 ☐ ☐ REAR ☐ ☐ A2524R ☐ ☐ A2543 ☐ ☐ A2158 ☐ ☐ FRONT (BULKHEAD) ☐ FRONT UPPERDECK ☐ REAR UPPERDECK ☐
REMARKS			