

DRIVER	Kit Std. Setup EU Carpet		
DATE			
TRACK	Carpet <input checked="" type="radio"/>	Asphalt <input type="radio"/>	
TRACTION	LOW <input type="radio"/>	MEDIUM <input checked="" type="radio"/>	HIGH <input type="radio"/>
LAYOUT	SLOW <input checked="" type="radio"/>	MIXED <input type="radio"/>	FAST <input type="radio"/>
TEMP °C	AIR	TRACK	
ELECTRONICS			
ESC	ESC SET	MOTOR	
SERVO	RECEIVER	BATTERY	
TIRES			
BRAND	Ride		
TYPE	ETS		
ADDITIVE	MR33 V4		
WARMER °C	FRONT	REAR	
TIME(min)	FRONT	10	REAR 10
SHOCK ABSORBERS			
PISTON	FRONT	Std.	REAR Std.
SHOCK CASE	Std.		
OIL	350 350		
SPRING	6.0P 6.75		
LENGTH		9.5	
ANTI ROLL BAR FRONT/REAR			
FRONT	1.1	REAR	1.1
DIFF	<input checked="" type="radio"/>	SPOOL	<input type="radio"/>
OIL CST	1.000K		
GEAR RATIO (T)Spur/(T)Pinion*1,9=Ratio			
PINION		SPUR	
AERODYNAMIC SETTINGS			
BODY TYPE	Blitz MK9		
WING TYPE	Std.		
WING POS	(mm)	Std.	
BODY POSITION (see picture below)	(mm) \leftrightarrow horizontal	55	
FRONT BODY HEIGHT & POSITION	REAR BODY POST A2407C	<input checked="" type="radio"/>	REAR BODY POST A2416B <input type="radio"/>
(mm) vertical \updownarrow	59	(mm)	57

STEERING LIMITER

A2304 (5mm)

A2305 (5.5mm)

A2306 (6mm)

STEERING ANGLE IN°

STEERING ANGLE OUT°

A2427 USED

YES

NO

A2427 SHIM(mm)

UPPER ARM POS. FR(mm)

FF(mm)

LOWER ARM POS. FR(mm)

FF(mm)

SHOCK POS (mm)

STEERING ROD POS (mm)

SHIM UPRIGHT L (mm)

UPPERARM POS. (CASTER)

REAR/5°

FRONT/4°

SHIM UPRIGHT T(mm)

CAMBER/°

TOE OUT/°

OFFSET (mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

A2529 POSITION

INSIDE

OUTSIDE

A2530 POSITION

INSIDE

OUTSIDE

ACKERMANN SHIM (mm)

SHIM S HORN (mm)

LENGTH S HORN (mm)

REAR TOE ROD POS

FRONT

REAR

UPPERARM POS. (CASTER)

FRONT/-4°

REAR/-3°

SHIM UPRIGHT T (mm)

CAMBER/°

TOE IN/°

OFFSET (mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

UPPER ARM POS. RF(mm)

RR(mm)

LOWER ARM POS. RF(mm)

RR(mm)

SHOCK POS (mm)

TOE ROD POS (mm)

SHIM UPRIGHT L (mm)

UPPERARM POS. (CASTER)

FRONT/-4°

REAR/-3°

SHIM UPRIGHT T (mm)

CAMBER/°

TOE IN/°

OFFSET (mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

A2430(40g)

A2432(85g)

BATTERY POSITION

WEIGHT POSITIONS (g)

A

B

C

D

E

FRONT/REAR WEIGHT DISTRIBUTION HOLE#

A2419

A2419 SCREW

MM SCREW

BELT TENSION

1pc. UPPERDECK TYPE

OVERALL WEIGHT(g)

SHOCK TOWER

A2524F

A2542

A2524R

A2543

A2158

UPPERDECK SCREW

UPPERDECK BEARING

2pc. UPPERDECK

FRONT SCREWS

REAR SCREWS

FRONT (BULKHEAD)

FRONT (2pc.UPPERDECK)

REAR (UPPERDECK)

REMARKS