

DRIVER		
DATE		
TRACK	Carpet <input type="radio"/> Asphalt <input type="radio"/>	
TRACTION	<input type="radio"/> LOW <input type="radio"/> MEDIUM <input type="radio"/> HIGH	
LAYOUT	<input type="radio"/> SLOW <input type="radio"/> MIXED <input type="radio"/> FAST	
TEMP °C	AIR	TRACK
ELECTRONICS		
ESC	ESC SET	MOTOR
SERVO	RECEIVER	BATTERY
TIRES		
BRAND		
TYPE		
ADDITIVE		
WARMER °C	FRONT	REAR
TIME(min)	FRONT	REAR
SHOCK ABSORBERS		
PISTON	FRONT	REAR
SHOCK CASE		
OIL		
SPRING		
LENGTH		
ANTI ROLL BAR FRONT/REAR		
FRONT		REAR
DIFF	<input type="radio"/>	SPOOL
OIL CST		
GEAR RATIO		
<small>(T)Spur/(T)Pinion*1,9=Ratio</small>		
PINION		SPUR
AERODYNAMIC SETTINGS		
BODY TYPE		
WING TYPE		
WING POS	(mm)	
BODY POSITION (see picture below)	(mm) \leftrightarrow horizontal	
FRONT BODY HEIGHT & POSITION	REAR BODY POST A2407C	REAR BODY POST A2416B
(mm) vertical \updownarrow	(mm)	(mm)

STEERING LIMITER

A2304 (5mm)

A2305 (5.5mm)

A2306 (6mm)

STEERING ANGLE IN°

STEERING ANGLE OUT°

A2427 USED

YES NO

A2427 SHIM(mm)

UPPER ARM POS. FR(mm)

FF(mm)

LOWER ARM POS. FR(mm)

FF(mm)

SHOCK POS (mm)

STEERING ROD POS (mm)

SHIM UPRIGHT L (mm)

UPPERARM POS. (CASTER)

REAR/5° FRONT/4°

SHIM UPRIGHT T(mm)

CAMBER/°

TOE OUT/°

OFFSET (mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

FRONT

A2529 POSITION

INSIDE

OUTSIDE

A2530 POSITION

INSIDE

OUTSIDE

ACKERMANN SHIM (mm)

SHIM S HORN (mm)

LENGTH S HORN (mm)

TYPE SERVO HORN

REAR TOE ROD POS

FRONT REAR

UPPERARM POS. (CASTER)

FRONT/-4° REAR/-3°

SHIM UPRIGHT T (mm)

CAMBER/°

TOE IN/°

OFFSET (mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

REAR

A2430(40g)

A2432(85g)

WEIGHT POSITIONS (g)

BELT TENSION

1pc. UPPERDECK TYPE

OVERALL WEIGHT(g)

BATTERY POSITION

A2419

A2419 SCREW

MM SCREW

A **E**

FRONT/REAR WEIGHT DISTRIBUTION HOLE#

SHOCK TOWER

A2524F A2542

A2524R A2543

A2158

FRONT (BULKHEAD)

FRONT (2pc.UPPERDECK)

REAR (UPPERDECK)

UPPERDECK SCREW

UPPERDECK BEARING

2pc. UPPERDECK

FRONT SCREWS

REAR SCREWS

REMARKS

Find more setup's under www.mugenseiki.co.jp